

EROSION CONTROL PLAN & SCHEDULE

SILT FENCE TO BE INSTALLED PRIOR TO ANY EARTHWORK ACTIVITY, IN LOCATION SHOWN ON PLANS, PER DETAIL.

STONE SHALL BE INSTALLED IN FUTURE DRIVEWAY AREA 20 FEET WIDE AND 30 FEET LONG TO PREVENT VEHICLES FROM TRACKING SEDIMENT OFF THIS SITE INGRESS AND EGRESS TO BE LIMITED TO THIS AREA ONLY.

SEDIMENT CONTROL PRACTICES SHALL BE FUNCTIONAL THROUGHOUT ALL PHASES OF EARTH DISTURBING ACTIVITY. SETTLING FACILITIES, PERIMETER CONTROLS, AND OTHER PRACTICES INTENDED TO TRAP SEDIMENT SHALL BE IMPLEMENTED AS THE FIRST STEP OF GRADING AND WITHIN SEVEN (7) DAYS FROM THE START OF GRUBBING. THEY SHALL CONTINUE TO FUNCTION UNTIL THE DISTURBED AREA IS PERMANENTLY RESTABILIZED.

UNDISTURBED AREAS SHALL HAVE SOIL STABILIZATION WITHIN NO MORE THAN SEVEN (7) DAYS IF THEY ARE TO REMAIN DORMANT UNDISTURBED FOR MORE THAN THIRTY-FIVE (35) DAYS. PERMANENT OR TEMPORARY SOIL STABILIZATION SHALL BE APPLIED TO DISTURBED AREAS WITHIN NO MORE THAN SEVEN (7) DAYS AFTER FINAL GRADE IS REACHED ON ANY PORTION OF THE SITE, AND SHALL ALSO BE APPLIED WITHIN NO MORE THAN SEVEN (7) DAYS TO DISTURBED AREAS WHICH MAY NOT BE AT FINAL GRADE, BUT WILL REMAIN DORMANT FOR LONGER THAN THIRTY-FIVE (35) DAYS.

STABILIZATION OF CRITICAL AREAS WITHIN 50 FEET OF ANY STREAM OR WETLAND SHALL BE TEMPORARILY STABILIZED WITHIN TWO (2) DAYS OF DISTURBANCE. AREA WILL REMAIN INACTIVE FOR FOURTEEN (14) DAYS OR LONGER. CONSTRUCTION VEHICLES SHALL AVOID STREAMS AND THEIR BUFFER AREAS. IF ANY ACTIVE DRAINAGE WAY MUST BE CROSSED BY CONSTRUCTION VEHICLES REPEATEDLY DURING CONSTRUCTION, AN APPROVED TEMPORARY STREAM CROSSING SHALL BE CONSTRUCTED.

SOIL STOCKPILES SHALL BE STABILIZED OR PROTECTED TO PREVENT SOIL LOSS. STABILIZATION SHALL BE REQUIRED IF STOCKPILES ARE LOCATED WITHIN CRITICAL AREAS NEAR STREAM OR WETLANDS, OR IF DETERMINED BY THE ADMINISTRATOR THAT SEDIMENT FROM STOCKPILES WILL LEAVE THE SITE.

SEDIMENT AND EROSION CONTROLS SHALL BE INSPECTED BY THE OWNER OR HIS/HER AGENT EVERY SEVEN (7) DAYS AND WITHIN 24 HOURS OF A 0.5" OR GREATER RAINFALL EVENT. A WRITTEN LOG OF THESE INSPECTIONS AND IMPROVEMENTS TO CONTROLS SHALL BE KEPT ON SITE. THESE INSPECTIONS SHALL INCLUDE THE DATE OF INSPECTION, NAME OF INSPECTOR, WEATHER CONDITIONS, THE ACTIONS TAKEN TO CORRECT ANY PROBLEMS AND THE DATE ACTIONS WERE TAKEN.

MEASURES SHALL BE TAKEN TO PREVENT SOIL TRANSPORT ONTO SURFACES WHERE RUNOFF IS NOT CHECKED BY SEDIMENT CONTROLS, OR ONTO PUBLIC ROADS. WHERE SOIL IS TRANSPORTED ONTO A PUBLIC ROAD SURFACE, THE ROADS SHALL BE CLEANED THOROUGHLY AT THE END OF EACH DAY, OR MORE FREQUENTLY AS NECESSARY. SOIL SHALL BE REMOVED FROM PAVED SURFACES BY SHOVELING OR SWEEPING. STREET WASHING SHALL BE ALLOWED ONLY AFTER MOST SEDIMENT HAS BEEN REMOVED BY SHOVELING OR SWEEPING.



THE ABOVE SPECIFIED EROSION CONTROL STANDARDS ARE GENERAL GUIDELINES AND SHALL NOT LIMIT THE RIGHT OF THE COUNTY TO IMPOSE, AT ANY TIME, ADDITIONAL, MORE STRINGENT REQUIREMENTS, NOR SHALL THE STANDARDS LIMIT THE RIGHT OF THE COUNTY TO WAIVE, IN WRITING, INDIVIDUAL REQUIREMENTS.

PERMANENT SEEDING TO BE INSTALLED AFTER ALL CONSTRUCTION ACTIVITY IS COMPLETE.

SEEDING AND MULCHING NOTES:
SEEDING CONTROL SHALL BE ACCOMPLISHED BY SEEDING AND MULCHING IMMEDIATELY UPON COMPLETION OF EXCAVATION OF FILL AND FINISHED GRADING IN ACCORDANCE WITH ITEM NO. 656 ODOT CONSTRUCTION AND MATERIAL SPECIFICATIONS OR AS DIRECTED BY THE ENGINEER.



THE FOLLOWING MIXTURE SHALL BE USED FOR SEEDING IN ACCORDANCE WITH ODOT ITEM 656.

KENTUCKY BLUE GRASS— 40%
CREEPING RED FESCUE— 40% 3#/1000 S.F.
PERENNIAL RYEGRASS— 20%
FERTILIZER— 20#/1000 S.F. (12-12-12)
MULCH—STRAW/ 3 TONS/ ACRE



EXISTING UNDERGROUND UTILITIES NOTE:
THE SIZE & LOCATION, BOTH HORIZONTAL AND VERTICAL, OF THE UNDERGROUND UTILITIES SHOWN HEREON, HAVE BEEN OBTAINED BY A SEARCH OF AVAILABLE RECORDS. VERIFICATION BY FIELD OBSERVATION HAS BEEN CONDUCTED WHERE PRACTICAL. HOWEVER, LDC INC. DOES NOT GUARANTEE THE COMPLETENESS NOR ACCURACY THEREOF.

2 WORKING DAYS
BEFORE YOU DIG
CALL TOLL FREE 800-362-2764
UNDER UTILITIES PROTECTION SERVICE



I, THE UNDERSIGNED, HEREBY CERTIFY THAT THE TOPOGRAPHY, INDICATED BY 1", 1", OR 2" CONTOURS, AND ELEVATIONS SHOWN HEREON, REPRESENT AN ACTUAL FIELD SURVEY MADE BY ME OR ONE OF MY DAY OF SURVEY, 2004, AND THAT THE ELEVATIONS WERE TAKEN AT APPROPRIATE INTERVALS AND THAT AS OF THAT DATE THEY EXISTED AS INDICATED HEREON.

S/L11 House Summary
Model#2002, EL#7
3-Cor Left/Right Entry
w/ Walkout Type Bath
Survivor Opt. 4474m, 4m, 4m, 4m
Add#2076 Browning Ct.

SITE PLAN

For: **Pulte Homes Of Ohio**
8376 Morley Rd. **CONCORD, OHIO**
13 **Holden Ridge** 41
LOT No. **CONCORD** CITY/TOWNSHIP

LAND DESIGN consultants
www.LDCinc.net
ENGINEERS • PLANNERS • SURVEYORS
8285 East Avenue, Dayton, Ohio 45424
TEL: (937) 233-9463 FAX: (937) 233-9464
(937) 233-9465 FAX: (937) 233-9466


DESIGN CERTIFICATION
THIS PLAN WAS PREPARED BY ME AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

CHECK LIST
1. ALL REQUIRED PERMITS OBTAINED
2. ALL REQUIRED NOTICES SERVED
3. ALL REQUIRED FEES PAID
4. ALL REQUIRED RECORDS MAINTAINED
5. ALL REQUIRED INSPECTIONS COMPLETED
6. ALL REQUIRED CORRECTIONS MADE
7. ALL REQUIRED AS-BUILT RECORDS MAINTAINED
8. ALL REQUIRED EROSION CONTROL MEASURES INSTALLED
9. ALL REQUIRED SEEDING AND MULCHING COMPLETED
10. ALL REQUIRED STABILIZATION COMPLETED

"AS BUILT" CERTIFICATION
I HEREBY CERTIFY THAT THE AS-BUILT INFORMATION IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

NAME	DATE	BY	DATE
LEGEND	G.S.V.	DATE BY FIELD	DATE
1. 1" = 20' SCALE	1. 1" = 20' SCALE	1. 1" = 20' SCALE	1. 1" = 20' SCALE
2. 1" = 20' SCALE	2. 1" = 20' SCALE	2. 1" = 20' SCALE	2. 1" = 20' SCALE
3. 1" = 20' SCALE	3. 1" = 20' SCALE	3. 1" = 20' SCALE	3. 1" = 20' SCALE
4. 1" = 20' SCALE	4. 1" = 20' SCALE	4. 1" = 20' SCALE	4. 1" = 20' SCALE
5. 1" = 20' SCALE	5. 1" = 20' SCALE	5. 1" = 20' SCALE	5. 1" = 20' SCALE
6. 1" = 20' SCALE	6. 1" = 20' SCALE	6. 1" = 20' SCALE	6. 1" = 20' SCALE
7. 1" = 20' SCALE	7. 1" = 20' SCALE	7. 1" = 20' SCALE	7. 1" = 20' SCALE
8. 1" = 20' SCALE	8. 1" = 20' SCALE	8. 1" = 20' SCALE	8. 1" = 20' SCALE
9. 1" = 20' SCALE	9. 1" = 20' SCALE	9. 1" = 20' SCALE	9. 1" = 20' SCALE
10. 1" = 20' SCALE	10. 1" = 20' SCALE	10. 1" = 20' SCALE	10. 1" = 20' SCALE

BENCHMARK: B.M. = T.B.M. Set On Top Of House Located In Front Of S/L 11, Elev. = 834.00



Grading Plan Approved as shown and/or noted
JAMES R. GILLS, P.E.
Lake County Engineer
By: **JEB** Date: **3/19/02**