





Seeding Dates	Species	Lb./1,000 ft. ²	Per Aç.	
March 1 to August 15	Oats	з .	4 bushel	
·	Tall Fescue	1	40 lb.	
	Annual Ryegress	1	40 lb.	
	Perennial Ryegrass	1	40 lb.	
	Tell Fescue	1	40 lb.	
	Annual Ryegrass	1	40 lb.	
August 16 to November 1	Rve	3	2 bushel	
	Tell Fescue	1	40 lb.	
	Annual Ryegrass	1	40 lb.	
	Wheat	3	2 bushel	
	Tall Fescue	1	40 lb.	
	Annual Ryegrass	1	40 lb.	
	Perennial Ryegrass	1	40 lb.	
	Tall Fescue	1	40 lb.	
	Annual Ryegrass	1	40 lb.	
November 1 to Spring Seeding	Use mulch only, sodding practices or dormant seeding.			

Erosion and Sediment Control Schedule

A stone access drive complete with under lying geo-textile fabric (20 feet wide and 50 feet long) for ingress and egress at the site shall be installed. This drive shall be the only entrance and exit to the site.

Silt Fence

A silt fence shall be installed prior to any earthwork activities at the site in the locations shown on the site plan as well as along the front of any lot that slopes towards the street.

Temporary Seeding
Disturbed areas of the site that are to remain idle for more than thirty(30) days shall be properly seeded and straw mulched within seven(7) days of completion of intitial grading. Temporary seeding and mulching as a thirty(30) foot strip of the entire front of the lot shall be maintained on the site once initial grading is complete.

Stabilization of critical areas within fifty(50) feet of any stream or wetland shall be complete within two(2) days of the disturbance if the site is to remain inactive for longer than fourteen(14) days.

Straw—mulch shall be applied at a rate of 1 bale per every ten (10) feet of curb, at a width of thirty(30) feet to the entire length of the lot. Wood chips may also be used but must be spread at a minimum depth of four inches over the thirty—foot width and must be accompanied by a properly installed silt fence.

<u>Maintenance</u>

Erosion and sediment controls shall be inspected every seven(7) days or within 24 hours of a 0.5" or greater rainfall event. Necessary repairs shall be made at this time.

> "I, the undersigned hereby certify that this topography indicated by 6", 1', or 2' contours, and elevations shown hereon represent an actual field survey made by me on the 570 day of 1424,20 65 and that the elevations were taken at appropriate intervals and that as of that date they existed as indicated hereon."

2							
	CONCORT TOWS	nP, Conce	COUNTY	, OHIO			
	FOR: ALEXADORA HOMES						
ļ							
	ADDRESS	STREET	CITY	22			
	SUBOMSION 42-33 N	AME TRA		REET			
		34 HUL COLATION					
	SUBLOT NO. ST		PG. PE	M. PARCEL NO.			
		LEGEND	. COMOO O				
	SANITARY MANHOLE	- O EXIST. ELE	1998 =5	PROP. ELEV.			
ı	STORM MANHOLE	AS BUILT &	NOTAVALE	(60)			
	INLET OR CATCH BASIN		INDICATES				
	EXISTING CONTOURS		DIRECTION OF				
	PROPOSED CONTOURS-	- ▼	SURFACE DRAINA	Œ			
	REMARKS ALL BOUNDARY DATA SHOWN WAS OBTAINED FROM (DEEDS, RECORDED SUBDIVISION PLAT OR OTHER PUBLIC RECORDS) LOCATIONS AS SHOWN OF ADJACENT WELLS AND SEPTIC TANKS OBTAINED FRO LAKE COUNTY HEALTH DEPARTMENT						
	THIS PLAT WAS PR	ON CERTIFICEPARED BY ME.	AND IS CORR	ECT			
	TO THE BEST OF M		ND BELIEF.	2			
	- FICE	BURNETOR	AC6343	W NO.			
	/ (HECK LIST					
	NO. OF BEDROOMS		N SIZE, LOCATION				
1	DIMENSIONS BEARINGS	I SAN. SEWE	R SIZE % GR. LOC. XST. ELEV. INV. EL	ev.			
ı	TIE TO NEAREST STREET SUBLOT NO. PARCEL NO.	SAN. CON	i, size, loc. depti	H			
	SURROUNDING OWNERS BLDG. DIMENSIONS FIN GR.	STORM MH	ver siže % or. lo . cast elev. inv. i	LEV.			
Į	BLDQ. TIES FL'R. GRADES APRON TYPE WIDTH THICKNESS	GAS LINE (CORADE CURBS LOC. SIZE PRESSUR	Æ			
	SIDEWALK TYPE WIDTH THICKNESS CULVERT TYPE DIA., LENGTH	WELL LOCA	ek location & DU ITION				
	ROCK OUTCROPPINGS	ISOLATION	RADIUS FROM WELL				
	REVISIONS	***					
	NO. DATE BY		PREPARED BY:	NATES IN			
		ABCOCK · JONE		MILD, INC			
	2		ESVILLE, OHIO				
	3 DRAWN B	DY	PHON	440-357-181			
1	4 CHKD.	DATE 7	DRAW!	NG NO.			

"AS BUILT" CERTIFICATION

I, HEREBY CERTIFY THAT THE CIRCLED GRADES ARE EXISTING
FINISH GRADES CHECKED IN THE FIELD ON ________, 20_____
AND ARE CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REDISTERED SURVEYOR

REG. NO.

EXISTING UTILITIES NOTE:
THE SIZE AND LOCATION, BOTH HORIZONTAL AND VERTICAL OF THE UNDERGROUND UTILITIES SHOWN HEREON, HAVE BEEN OBTAINED BY A SEARCH OF AVAILABLE RECORDS. VERIFICATION BY FIELD OBSERVATION HAS BEEN CONDUCTED WHERE PRACTICAL, HOWEVER, BABCOCK, JONES AND ASSOCIATES INC. DOES NOT GUARANTEE THE COMPLETENESS NOR ACCURACY THEREOF.

