





Seeding Dates	Species	Lb./1,000 ft. <sup>2</sup>	Per Ac.	
March 1 to August 15	Oats	3 .	4 bushel	
	Tall Fescue	1	40 lb.	
	Annual Ryagrass	1	40 lb.	
	Perennial Ryegrass	1	40 lb.	
	Tall Fescue	1	40 lb.	
	Annual Ryegrass	1	40 lb.	
August 16 to November 1	Rye	3	2 bushel	
_	Tell Fescue	i [	40 lb.	
	Annual Ryegrass	1	40 lb.	
	Wheat	3	2 bushel	
	Tall Fescue	1	40 lb.	
	Annual Ryegrass	1	40 lb.	
	Perennial Ryagrass	1	40 lb.	
	Tall Fescue	1	40 lb.	
	Annual Byagrass	1	40 lb.	
lovember 1 to Spring Seeding	Hee mulch only codd	ing practices or dorma	er seedige	

Erosion and Sediment Control Schedule

A stone access drive complete with under lying geo-textile fabric (20 feet wide and 50 feet long) for ingress and egress at the site shall be installed. This drive shall be the only entrance and exit to the site.

Silt Fence

A silt fence shall be installed prior to any earthwork activities at the site in the locations shown on the site plan as well as along the front of any lot that slopes towards the street.

Temporary Seeding

Disturbed areas of the site that are to remain idle for more than thirty(30) days shall be properly seeded and straw mulched within seven(7) days of completion of intitial grading. Temporary seeding and mulching as a thirty(30) foot strip of the entire front of the lot shall be maintained on the site once initial grading is complete.

Stabilization of critical areas within fifty(50) feet of any stream or wetland shall be complete within two(2) days of the disturbance if the site is to remain inactive for longer than fourteen(14) days.

Mulching
Straw-mulch shall be applied at a rate of 1 bale per every ten (10) feet of curb, at a width of thirty(30) feet to the entire length of the lot. Wood chips may also be used but must be spread at a minimum depth of four inches over the thirty-foot width and must be accompanied by a properly installed silt

<u>Maintenance</u>

Erosion and sediment controls shall be inspected every seven(7) days or within 24 hours of a 0.5" or greater rainfall event. Necessary repairs shall be made at this time.

"I, the undersigned hereby certify that
this topography indicated by 6", 1', or 2'
contours, and elevations shown hereon
represent an actual field survey made by
me on the 1014 day of 501,20 04
and that the elevations were taken at
appropriate intervals and that as of that
date they existed as indicated hereon."

Reg. No.

CONCORD TOWNSHIP, LAKE COUNTY, OHIO for: ERICKSON CONSTRUCTION ADDRESS STREET ZIP CITY ELLISON (REEK TRACT SUBDIVISION 37-17 WOL-PG. ELLISON CLEEK SUBLOT NO. PERM. PARCEL NO. STREET VOL-PG. LEGEND ||EXIST. ELEV. 5=100.0 = 2 PROP. ELEV. SANITARY MANHOLE ---STORM MANHOLE AS BUILT ELEVATION DIRECTION OF EXISTING CONTOURS -SURFACE DRAINAGE PROPOSED CONTOURS -REMARKS ALL BOUNDARY DATA SHOWN WAS OBTAINED FROM (DEEDS, RECORDED SUBDIVISION PLAT OR OTHER PUBLIC RECORDS) LOCATIONS AS SHOWN OF ADJACENT WELLS AND SEPTIC TANKS OBTAINED FROM LAKE COUNTY HEALTH DEPARTMENT **DESIGN CERTIFICATION** THIS PLAT WAS PREPARED BY ME, AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF. #6343 REGISTRATION NO. NAME / CHECK LIST NO. OF BEDROOMS
DIMENSIONS
BEARINGS
TIE TO NEAREST STREET
SUBLOT NO. PARCEL NO. VATER MAIN SIZE, LOCATION
SAN. SEWER SIZE % GR. LOC.
SAN. MH. CAST. ELEV. INV. ELEV.
SAN. CONN. SIZE, LOC. DEPTH
STORM SEWER SIZE % GR. LOC.
STORM MH. CAST ELEV. INV. ELEV. SURROUNDING OWNERS BLDG. DIMENSIONS FIN GR. PAY'T TYPE GRADE CURBS
GAS LINE LOC. SIZE PRESSURE
SEPTIC TANK LOCATION & DUPLICATION AREA
WELL LOCATION BLDG. TIES FL'R. GRADES APRON TYPE WIDTH THICKNESS SIDEWALK TYPE WIDTH THICKNESS CULVERT TYPE DIA., LENGTH ISOLATION RADIUS FROM WELL ROCK OUTCROPPINGS

	REVISIONS								
ю.	DATE	BY	PLAN PREPARED BY: BABCOCK · JONES & ASSOCIATES, INC						
1			BA	BCOCF	C - JONE	ES & AS	SSOCIATES, INC		
2			PAINESVILLE, OHIO						
3			DRAWN BY	BP	SCALE		PHONE NO. 440357-18		
4			снкъ.	HT	DATE 9	16/04	DRAWING NO.		
5			CREW CHIEF		APP'D	<del>X7</del>	00-265-90		

"AS BUILT" CERTIFICATION
I, HEREBY CERTIFY THAT THE CIRCLED GRADES ARE EXISTING FINISH GRADES CHECKED IN THE FIELD ON. AND ARE CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED SURVEYOR

REG. NO.

THE SIZE AND LOCATION, BOTH HORIZONTAL AND VERTICAL OF THE UNDERGROUND UTILITIES SHOWN HEREON, HAVE BEEN OBTAINED BY A SEARCH OF AVAILABLE RECORDS. VERIFICATION BY FIELD OBSERVATION HAS BEEN CONDUCTED WHERE PRACTICAL, HOWEVER, BABCOCK, JONES AND ASSOCIATES INC. DOES NOT GUARANTEE THE COMPLETENESS NOR ACCURACY THEREOF.

