





seeding Dates	Species	Lb./1,000 ft. <sup>2</sup>	Per Ac.
March 1 to August 15	Oats	3 ·	4 bushel
	Tall Fescue	1	40 lb.
	Annual Ryegress	1	40 lb.
	Perennial Ryegrass Tall Fescue Annual Ryegrass	1 1 1	40 lb. 40 lb. 40 lb.
August 16 to November 1	Rye	3	2 bushel
	Tell Fescue	1	40 lb.
	Annual Ryegrass	1	40 lb.
	Wheat	3	2 bushel
	Tall Fescue	1	40 lb.
	Annual Ryegrass	1	40 lb.
	Perennial Ryegrass Tell Fescue Annual Ryegrass	1 1 1	40 lb. 40 lb. 40 lb.

Eroslon and Sediment Control Schedule

# Ingress-Egress

A stone access drive complete with under lying geo-textile fabric (20 feet wide and 50 feet long) for ingress and egress at the site shall be installed. This drive shall be the only entrance and exit to the site.

A silt fence shall be installed prior to any earthwork activities at the site in the locations shown on the site plan as well as along the front of any lot that slopes towards the street.

Temporary Seeding
Disturbed areas of the site that are to remain idle for more than thirty(30) days shall be properly seeded and straw mulched within seven(7) days of completion of intitial grading. Temporary seeding and mulching as a thirty(30) foot strip of the entire front of the lot shall be maintained on the site once initial grading is complete.

Stabilization of critical areas within fifty(50) feet of any stream or wetland shall be complete within two(2) days of the disturbance if the site is to remain inactive for longer than fourteen(14) days.

Straw—mulch shall be applied at a rate of 1 bale per every ten (10) feet of curb, at a width of thirty(30) feet to the entire length of the lot. Wood chips may also be used but must be spread at a minimum depth of four inches over the thirty-foot width and must be accompanied by a properly installed silt fence.

Erosion and sediment controls shall be inspected every seven(7) days or within 24 hours of a 0.5" or greater rainfall event. Necessary repairs shall be made at this time.

> "I, the undersigned hereby certify that this topography indicated by 6", 1', or 2' contours, and elevations shown hereon represent an actual field survey made by me on the 2574 day of Julie, 20 04 and that the elevations were taken at appropriate intervals and that as of that date they existed as indicated hereon."

Reg. No.

┨	_	_							
ĺ	CONCORD TOWNSHIP, LAKE COUNTY, OHIO								
l	for: KAY Homes								
l	101:	CLIENT	OWNER						
	ADDRESS	ADDRESS S			TREET CITY ZIP				
	ELUS OR CREE		- TR	ACT					
	SUBDIVISION 44-2	G. STANEWYCK	. —		STREET				
	SUBLOT NO.	STREET		XL-PG.	PERM. PARCEL NO.				
	LEGEND								
	SANITARY MANHOLE	<b>0</b>	EXIST. EL	EV.~> = 108.6	PROP. ELEV.				
l	STORM MANHOLE — — INLET OR CATCH BASIN —		AS BUILT	ELEVATION	(100.0)				
l	HYDRANT			INDICATES					
•	EXISTING CONTOURS —	<del></del>		DIRECTION ( SURFACE D					
-	V								
	REMARKS ALL BOUNDARY DATA SHOWN WAS OBTAINED FROM (DEEDS, RECORDED								
	SUBDIVISION PLAT OR OTHER PUBLIC RECORDS)								
	LOCATIONS AS SHOWN OF ADJACENT WELLS AND SEPTIC TANKS OBTAINED FROM LAKE COUNTY HEALTH DEPARTMENT								
-		SECION OF		O A TI O N	• • • • • • • • • • • • • • • • • • • •				
		DESIGN CI Vas preparei							
١	THIS PLAT WAS PREPARED BY ME, AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.								
1	NAME /	May 1	NEYOR		1743 Tration no.				
			∠LIST		HATION IVO				
	NO, OF BEDROOMS DIMENSIONS		WATER MA	VIN SIZE, LOCA					
	BEARINGS TIE TO NEAREST STREET		SAN. MH.	ER SIZE % GR. CAST. ELEV. II	vv. elev.				
	SUBLOT NO. PARCEL NO. SURROUNDING OWNERS	SAN. CONN. SIZE, LOC. DEPTH STORM SEWER SIZE % GR. LOC. STORM MH. CAST ELEV. INV. ELEV.							
11	BLDG. DIMENSIONS FIN CR. BLDG. TIES FL'R. GRADES		PAV'T TYP	E GRADE CUR! LOC. SIZE PRE	BS				
	APRON TYPE WIDTH THICKN SIDEWALK TYPE WIDTH THIC THI VERT TYPE INA LEBACT	XNESS		NK LOCATION	& DUPLICATION AREA				
CULVERT TYPE DIA., LENGTH ROCK OUTCROPPINGS  WELL LOCATION ISOLATION RADIUS FROM WELL									
-	REVISIONS  DATE BY	( )	PI AN	בי השלים בי	<i>γ</i> .				
۴	1 BY	DATE BY PLAN PREPARED BY:  BABCOCK · JONES & ASSOCIATES, INC.							
H	2	PAINESVILLE, OHIO							

00-265-98 "AS BUILT" CERTIFICATION

I, HEREBY CERTIFY THAT THE CIRCLED GRADES ARE EXISTING
FINISH GRADES CHECKED IN THE FIELD ON \_\_\_\_\_\_\_, 20\_\_\_\_\_
AND ARE CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

E6/30/04

REGISTERED SURVEYOR

REG. NO.

ione no. 440-357-1811

EXISTING UTILITIES NOTE:
THE SIZE AND LOCATION, BOTH HORIZONTAL AND VERTICAL
OF THE UNDERGROUND UTILITIES SHOWN HEREON, HAVE BEEN
OBTAINED BY A SEARCH OF AVAILABLE RECORDS,
VERIFICATION BY FIELD OBSERVATION HAS BEEN CONDUCTED
WHERE PRACTICAL, HOWEVER, BABCOCK, JONES AND ASSOCIATES
INC. DOES NOT GUARANTEE THE COMPLETENESS NOR ACCURACY
THEREOF.

