



SILT FENCE DETAIL

TEMPORARY SEEDING SPECIFICATIONS

OATES		
TALL FESCUE ANNUAL RYEGRASS	3 1 1	4 BUSHEL 40 lb. 40 lb.
PERENNIAL RYEGRASS	1	40 lb.
TALL FESCUE	1	40 lb.
ANNUAL RYEGRASS	1	40 lb.
RYE	3	2 BUSHEL
TALL FESCUE	1	40 lb.
ANNUAL RYEGRASS	1	40 lb.
Wheat	3	2 BUSHEL
Tall Fescue	1	40 lb.
Annual Ryegrass	1	40 lb.
PERENNIAL RYEGRASS	1	40 lb.
TALL FESCUE	1	40 lb.
ANNUAL RYEGRASS	1	40 lb.
USE MULCH ONLY, SOD SEEDING.	DING PRACTICES OR DOI	RMANT
	PERENNIAL RYEGRASS TALL FESCUE ANNUAL RYEGRASS RYE TALL FESCUE ANNUAL RYEGRASS WHEAT TALL FESCUE ANNUAL RYEGRASS PERENNIAL RYEGRASS TALL FESCUE ANNUAL RYEGRASS USE MULCH ONLY, SOD SEEDING.	PERENNIAL RYEGRASS 1 TALL FESCUE 1 ANNUAL RYEGRASS 1 RYE 3 TALL FESCUE 1 ANNUAL RYEGRASS 1 WHEAT 3 TALL FESCUE 1 ANNUAL RYEGRASS 1 PERENNIAL RYEGRASS 1 PERENNIAL RYEGRASS 1 TALL FESCUE 1 ANNUAL RYEGRASS 1 USE MULCH ONLY, SODDING PRACTICES OR DOI

EROSION AND SEDIMENT CONTROL NOTES:

NGRESS-EGRESS

A STONE ACCESS DRIVE COMPLETE WITH UNDER LYING GEO-TEXTILE FABRIC (20 FEET WIDE AND 50 FEET LONG) FOR INGRESS AND EGRESS AT THE SITE SHALL BE INSTALLED. THIS DRIVE SHALL BE THE ONLY ENTRANCE AND EXIT TO THE SITE

ILT FENCE

ALL SILT FENCE SHALL BE INSTALLED PRIOR TO ANY EARTHWORK ACTIVITIES AT THE SITE IN THE LOCATIONS SHOWN ON THE SITE PLAN AS WELL AS ALONG THE FRONT OF ANY LOT THAT SLOPES TOWARDS THE STREET.

TEMPORARY SEEDING

DISTURBED AREAS OF THE SITE THAT ARE TO REMAIN IDLE FOR MORE THAN THIRTY (30) DAYS SHALL BE PROPERLY SEEDED AND STRAW MULCHED WITHIN SEVEN (7) DAYS OF COMPLETION OF INITIAL GRADING. TEMPORARY SEEDING AND MULCHING OF A THIRTY (30) FOOT STRIP OF ENTIRE FRONT OF LOT SHALL BE MAINTAINED ON THE SITE ONCE INITIAL GRADING IS COMPLETE.

MULCHING

STRAW-MULCH SHALL BE APPLIED AT A RATE OF 1 BALEPER EVERY TEN (10)
FEET OF CURB, AT A WIDTH OF THIRTY (30) FEET OF THE ENTIRE LENGTH OF THE
LOT. WOOD CHIPS MAY ALSO BE USED BUT MUST BE SPREAD AT A MINIMUM
DEPTH OF FOUR INCHES OVER THE THIRTY-FOOT WIDTH AND MUST BE
ACCOMPANIED BY A PROPERLY INSTALLED SILT FENCE.

<u>MAINTENANCE</u>

EROSION AND SEDIMENT CONTROLS SHALL BE INSPECTED EVERY SEVEN (7) DAYS WITHIN 24 HOURS OF A 0.5" OR GREATER RAINFALL EVENT. NECESSARY REPAIRS SHALL BE MADE AT THIS TIME.

ALL EROSION AND SEDIMENT CONTROL SPECIFICATIONS, APPLICATIONS, AND TIMETABLES ARE BASED ON THE DESCRIPTIONS AND STANDARDS OF THE OHIO DEPARTMENT OF NATURAL RECOURSES "RAINWATER AND LAND DEVELOPMENT MANUAL" AND CAN BE FOUND IN THE LAKE COUNTY EROSION AND SEDIMENT CONTROL RULES AS ADOPTED DECEMBER 21, 1999.