





Spacios	Lb./1,000 ft. ²	Par Ac.
Oats Tall Fescue Annual Ryagrass	3 · 1 1	4 bushel 40 lb. 40 lb.
Perennial Ryegrass Tall Fescue Annual Ryegrass	1 1 1	40 lb. 40 lb. 40 lb.
Rye Tall Fescue Annual Ryegrass	3 1 1	2 bushel 40 lb. 40 lb.
Wheat Tall Fescue Annual Ryegrass	3 1 1	2 bushel 40 lb. 40 lb.
Perennial Ryegrass Tall Fescue Annual Ryegrass	1 1 1	40 lb. 40 lb. 40 lb.
	Oats Tall Fescue Annual Ryegrass Perennial Ryegrass Tall Fescue Annual Ryegrass Rye Tall Fescue Annual Ryegrass Wheat Tall Fescue Annual Ryegrass Perennial Ryegrass Tall Fescue	Oats 3 · Tall Fescue 1 Annual Ryegrass 1 Perennial Ryegrass 1 Tall Fescue 1 Annual Ryegrass 1 Tall Fescue 1 Annual Ryegrass 1 Wheat 3 Tall Fescue 1 Annual Ryegrass 1 Perennial Ryegrass 1 Perennial Ryegrass 1 Tall Fescue 1 Annual Ryegrass 1 Tall Fescue 1 Annual Ryegrass 1 Tall Fescue 1 Tall Fescu

Erosion and Sediment Control Schedule

Ingress-Egress

A stone access drive complete with under lying geo—textile fabric (20 feet wide and 50 feet long) for ingress and egress at the site shall be installed. This drive shall be the only entrance and exit to the site.

Silt Fence

A silt fence shall be installed prior to any earthwork activities at the site in the locations shown on the site plan as well as along the front of any lot that slopes towards the street.

Temporary Seeding
Disturbed areas of the site that are to remain idle for more than thirty(30) days shall be properly seeded and straw mulched within seven(7) days of completion of intitial grading. Temporary seeding and mulching as a thirty(30) foot strip of the entire front of the lot shall be maintained on the site once initial grading is complete.

Stabilization of critical areas within fifty(50) feet of any stream or wetland shall be complete within two(2) days of the disturbance if the site is to remain inactive for longer than fourteen(14) days.

Straw—mulch shall be applied at a rate of 1 bale per every ten (10) feet of curb, at a width of thirty(30) feet to the entire length of the lot. Wood chips may also be used but must be spread at a minimum depth of four inches over the thirty-foot width and must be accompanied by a properly installed silt fence.

<u>Maintenance</u>

Erosion and sediment controls shall be inspected every seven(7) days or within 24 hours of a 0.5" or greater rainfall event. Necessary repairs shall be made at this time.

"I, the undersigned hereby certify that
this topography indicated by 6", 1', or 2'
contours, and elevations shown hereon
represent an actual field survey made by
me on the 15 day of 144,20 05
and that the elevations were taken at
appropriate intervals and that as of that
date they existed as indicated hereon."
/

2						
	MADISON TOWNSHIP.	LAK	E COUNT	Ү, ОНЮ		
	for: CAPUTO					
	CLIENT		OWNER			
	ADDRESS S	STREET	CITY	ZIP		
	SUBDINSION 33-15 NAME		ACT _			
	46 VOL-PG. FISHERMA	JIS 72/1)}	STREET		
ļ	SUBLOT NO. STREET	V	LPG. F	PERM. PARCEL NO.		
	LEG	SEND	n. 5% 100.0			
	SANITARY MANHOLE	II	EV5=108.8	2 PROP. ELEV.		
	STORM MANHOLE ————— INLET OR CATCH BASIN ———	AS BUILT	ELEVATION	(100.5)		
	HYDRANT		INDICATES DIRECTION OF			
	PROPOSED CONTOURS — — — —	1 5	SURFACE DRAI	VAGE		
	REMARKS ALL BOUNDARY DATA SHOWN WAS OBTAINED FROM (DEEDS, RECORDED SUBDIVISION PLAT OR OTHER PUBLIC RECORDS) LOCATIONS AS SHOWN OF ADJACENT WELLS AND SEPTIC TANKS OBTAINED FROM LAKE COUNTY HEALTH DEPARTMENT					
	DESIGN C					
	THIS PLAT WAS PREPARE TO THE BEST OF MY KNO			RECT		
	- tales 12 \$ 6343					
ŀ		IRVEYOR K LIST	REGISTRA	IION NO.		
	NO. OF BEDROOMS DIMENSIONS BEARINGS TIE TO NEAREST STREET SUBLOT NO. PARCEL NO. SURROUNDING OWNERS BLDG. DIMENSIONS FIN GR. BLDG. TIES FL'R. GRADES APRON TYPE WIDTH THICKNESS SIDEWALK TYPE WIDTH THICKNESS CULVERT TYPE DIA., LENGTH ROCK OUTCROPPINGS		WATER MAIN SIZE, LOCATION SAN. SEWER SIZE % GR. LOC. SAN. MH. CAST. ELEV. INV. ELEV. SAN. CONN. SIZE, LOC. DEPTH STORM SEWER SIZE % GR. LOC. STORM MH. CAST ELEV. INV. ELEV. PAV'T TYPE GRADE CURBS GAS LINE LOC. SIZE PRESSURE SEPTIC TANK LOCATION & DUPLICATION AREA WELL LOCATION ISOLATION RADIUS FROM WELL			
}	REVISIONS NO. DATE BY	PLAN	PREPARED BY:			
ł				CIATES, INC.		

97-268-46 "AS BUILT" CERTIFICATION I, HEREBY CERTIFY THAT THE CIRCLED GRADES ARE EXISTING FINISH GRADES CHECKED IN THE FIELD ON _______, 20_____ AND ARE CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED SURVEYOR

2

3

REG. NO.

IONE NO. 440-357-1811

PAINESVILLE, OHIO

EXISTING UTILITIES NOTE:
THE SIZE AND LOCATION, BOTH HORIZONTAL AND VERTICAL
OF THE UNDERGROUND UTILITIES SHOWN HEREON, HAVE BEEN
OBTAINED BY A SEARCH OF AVAILABLE RECORDS.
VERIFICATION BY FIELD OBSERVATION HAS BEEN CONDUCTED
WHERE PRACTICAL, HOWEVER, BABCOCK, JONES AND ASSOCIATES
INC. DOES NOT GUARANTEE THE COMPLETENESS NOR ACCURACY
THEREOF.

