

2 WORKING DAYS BEFORE YOU DIG CALL TOLL FREE 800-362-2764 OHIO UTILITIES PROTECTION SERVICE



"I, the undersigned hereby state that this topography, indicated by 1' contours, and the elevations shown hereon represent an actual field survey made by Foresight Engineering Group, Inc. on the 24 day of February, 2003 and that the elevations were taken at appropriate intervals and that as of that date they existed as indicated hereon."

2-26-03

Grading Plan Approved as shown and/or noted JAMES B. GILLS, P.E. Lake County Engineer

NOTES:
1. Down spouts shall be splashblocked.

2. Field verify depth of Existing Sanitary Lateral to determine availability of basement sanitary service.

SITE PLAN

R.L. Moore Builders

Lake Erie Shores

Painesville Township

LEGEND

Iron Pin in Monument

Manhole

Iron Pin Found

Water Service Valve

Iron Pin Set

Fire Hydrant

Curb Inlet

Light Pole

Telephone Box Electrical Box

Engineers &

Surveyors

Painesville Ohio 44.77

42 25

0hio STATE

SHEET NO.

1/2

- Sidewalk shall be 4" thick and in accordance with ODOT Item 608, Except where it passes through the driveway, the thickness shall be 6".
- 4. Utilities include Gas, Phone, Electric, and Cable. Contractor to field verify location and provide connection at utility.
- 5. Water Lateral to be 3/4" Copper Type "K".
- 6. Sanitary Lateral to be 6" Poly Vinyl Chloride SDR 26, 0 Ring Joints © 1.0% Min slope.
- 7. Storm Sewer Lateral to be 6" Poly Vinyl Chloride SDR 26, ● 1.0% Min slope.