


GREENSIDE DRIVE 60'

BENCHMARK - TOP STEM OF FIRE HYD.
IN FRONT OF SUBLT NO. 36, ELEV.=674.10



EX. STM. MH.
RIM=643.26
INV=637.61(15')
INV=637.57(18')

(216) 946-1761

Willoughby, Ohio 44094

Himebaugh and Novak

PREPARED BY:

QUENTIN S. HIMEBAUGH, P.E., No. 68820

"I HEREBY CERTIFY THAT THIS PLAN WAS PREPARED BY ME
AND IS CORRECT TO THE BEST OF MY KNOWLEDGE"

"I THE UNDERSIGNED HEREBY CERTIFY THAT THIS TOPOGRAPHY
INDICATED BY 'I' CONTOURS AND ELEVATIONS SHOWN HEREON
REPRESENTS AN ACTUAL SURVEY MADE BY ME ON THE 30th
DAY OF JAN., 1992 AND THE ELEVATIONS WERE TAKEN AT
APPROPRIATE INTERVALS AND AS OF THAT DAY THEY EXISTED
AS INDICATED HEREON.

CERTIFICATION

- GENERAL NOTES:
1. DRIVEWAY APRON TO BE 6" THICK
 2. BENCHMARK - TOP STEM OF FIRE HYDRANT LOCATED
IN FRONT OF SUBLT NO. 36, ELEV.=674.10

LEGEND



ROOF DRAINS
SHALL DISCHARGE
TO SPLASH BLOCKS.

Correcting Plan Approved
as shown and/or noted
THOMAS P. GILLES, P.E.
Lake County Engineer
By 6114 Date 1-11-94