

GENERAL NOTES:

IJ,

ROOF DRAINS
SHALL DISCHARGE
TO SPLASH BLOCKS.

Lake County Engineer

61H

Date On Page 1 1044

APPROVED APPROVED PAINESVILLE TOWNSHIP ZONING DEPARTMENT?

I. DRIVEWAY APRON TO BE 6" THICK
2. BENCHMARK - TOP STEM OF FIRE HYDRANT LOCATED
IN FRONT OF SUBLOT No. 33, ELEV.= 644.50

## LEGEND

EXISTING CONTOUR PROPOSED CONTOUR

PROPOSED ELEVATION

100.00 100.00

CERTIFICATION

"I THE UNDERSIGNED HEREBY CERTIFY THAT THIS TOPOGRAPHY INDICATED BY I' CONTOURS AND ELEVATIONS SHOWN HEREON REPRESENTS AN ACTUAL SURVEY MADE BY ME ON THE 30th DAY OF JAN, 1992 AND THE ELEVATIONS WERE TAKEN AT APPROPRIATE INTERVALS AND AS OF THAT DAY THEY EXISTED AS INDICATED HEREON.

"I HEREBY CERTIFY THAT THIS PLAN WAS PREPARED AND IS CORRECT TO THE BEST OF MY KNOWLEDGE" B¥

DAVID W

NOVAK,

20

7507

PREPARED BY:

## Himebaugh and Novak

(216)Surveyors and Site Consultants 8663 Tyler Boulevard Mentor, Ohio 44060-4346 6) 974-7670, (216) 255-5900 F FAX

SUBLOT No. 10 GREENSIDE DRIVE, PAINES VILLE TWP. ASHBOURINE SUBDIVISION, VOL. 12, PG. 4
SCHOENIGER BROS. CONSTRUCTION INC.
1" = 20'

SEPT. 016, 1994 DAVID W. NOVAK

9 004-

000