





·Species	Lb./1,000 ft. ²	Per Ac.
Oats Tall Fescue Annual Ryegress	3 · 1 1	4 bushel 40 lb. 40 lb.
Perennial Ryegrass Tall Fescue Annual Ryegrass	1 1 1	40 lb. 40 lb. 40 lb.
Rye Tali Fescue Annual Ryegrass	3 . 1 . 1	2 bushel 40 lb. 40 lb.
Wheat Tall Fescue Annual Ryegrass	3 1 1	2 bushel 40 lb. 40 lb.
Perennial Ryegrass Tall Fescue Annual Ryegrass	1 1	40 lb. 40 lb. 40 lb.
	Oats Tall Fescue Annual Ryegrass Perennial Ryegrass Tall Fescue Annual Ryegrass Rye Tall Fescue Annual Ryegrass Wheat Tall Fescue Annual Ryegrass Perennial Ryegrass Tall Fescue	Oats 3 Tall Fescue 1 Annual Ryegrass 1 Perennial Ryegrass 1 Tall Fescue 1 Annual Ryegrass 1 Rye 3 Tall Fescue 1 Annual Ryegrass 1 Wheat 3 Tall Fescue 1 Annual Ryegrass 1 Perennial Ryegrass 1 Perennial Ryegrass 1 Tall Fescue 1

Erosion and Sediment Control Schedule

Ingress-Egress

A stone access drive complete with under lying geo—textile fabric (20 feet wide and 50 feet long) for ingress and egress at the site shall be installed. This drive shall be the only entrance and exit to the site.

Silt Fence

A silt fence shall be installed prior to any earthwork activities at the site in the locations shown on the site plan as well as along the front of any lot that slopes towards the street.

Temporary Seeding

Disturbed areas of the site that are to remain idle for more than thirty(30) days shall be properly seeded and straw mulched within seven(7) days of completion of intitial grading.

Temporary seeding and mulching as a thirty(30) foot strip of the entire front of the lot shall be maintained on the site once initial grading is complete.

Stabilization of critical areas within fifty(50) feet of any stream or wetland shall be complete within two(2) days of the disturbance if the site is to remain inactive for longer than fourteen(14) days.

Mulching

Straw—mulch shall be applied at a rate of 1 bale per every ten (10) feet of curb, at a width of thirty(30) feet to the entire length of the lot. Wood chips may also be used but must be spread at a minimum depth of four inches over the thirty—foot width and must be accompanied by a properly installed silt fence.

<u>Maintenance</u>

Erosion and sediment controls shall be inspected every seven(7) days or within 24 hours of a 0.5" or greater rainfall event.

Necessary repairs shall be made at this time.

"I, the undersigned hereby certify that
this topography indicated by 6", 1', or 2
contours, and elevations shown hereon
represent an actual field survey made be me on the day of feets.,20 06
me on the day of 128.,20 06
and that the elevations were taken at
appropriate intervals and that as of tha
date they existed as indicated hereon."

Name Reg. No.

PANEOULLE TWY,	LAKE COUNTY, OHIO			
for: JEFF OLDSZ CLIENT OWNER				
ADDRESS S	TREET CITY ZIP			
HURSERY SUB, SUBDIVISION 6-144 NAME	TRACT STREET			
SUBLOT NO. STREET VOL-PG. PERM. PARCEL NO.				
LEGEND				
SANITARY MANHOLE	EXIST. ELEV. 5-100.0 PROP. ELEV.			
STORM MANHOLE	AS BUILT ELEVATION			
HYDRANT	INDICATES DIRECTION OF			
EXISTING CONTOURS — — — — — PROPOSED CONTOURS — — — —	SURFACE DRAINAGE			
REMARKS				
ALL BOUNDARY DATA SHOWN WAS OBTAINED FROM (DEEDS, RECORDED SUBDIVISION PLAT OR OTHER PUBLIC RECORDS)				
LOCATIONS AS SHOWN OF ADJACENT WELLS AND SEPTIC TANKS OBTAINED FROM LAKE COUNTY HEALTH DEPARTMENT				
DESIGN CERTIFICATION THIS PLAT WAS PREPARED BY ME, AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.				
NAME SU	RVEYOR REGISTRATION NO.			
/ ÇHÉCK LIST				
NO. OF BEDROOMS DIMENSIONS	WATER MAIN SIZE, LOCATION SAN. SEWER SIZE % GR. LOC.			
BEARINGS TIE TO NEAREST STREET SUBLOT NO. PARCEL NO.	SAN. MH. CAST. ELEV. INV. ELEV. SAN. CONN. SIZE, LOC. DEPTH			
SURROUNDING OWNERS BLDG. DIMENSIONS FIN GR.	STORM SEWER SIZE % GR. LOC. STORM MH. CAST ELEV. INV. ELEV.			
BLDG. TIES FL'R. GRADES APRON TYPE WIDTH THICKNESS	PAY'T TYPE GRADE CURBS GAS LINE LOC. SIZE PRESSURE			
SIDEWALK TYPE WIDTH THICKNESS CULVERT TYPE DIA., LENGTH ROCK OUTCROPPINGS	SEPTIC TANK LOCATION & DUPLICATION AREA WELL LOCATION ISOLATION RADIUS FROM WELL			
REVISIONS				
NO. DATE BY BARCO	PLAN PREPARED BY:			
1 3/30/86 1/17 BABCOCK JONES & ASSOCIATES, INC.				
DRAWN BY BD	SCALE PHONE NO.			
4 CHR'D. UST	- DATE 2/06 DRAWING NO.			
5 CREW	APP'D 187 06-012			

"AS BUILT" CERTIFICATION

I, HEREBY CERTIFY THAT THE CIRCLED GRADES ARE EXISTING
FINISH GRADES CHECKED IN THE FIELD ON ______, 20_____
AND ARE CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED SURVEYOR

REG. NO.

EXISTING UTILITIES NOTE:
THE SIZE AND LOCATION, BOTH HORIZONTAL AND VERTICAL
OF THE UNDERGROUND UTILITIES SHOWN HEREON, HAVE BEEN
OBTAINED BY A SEARCH OF AVAILABLE RECORDS.
VERIFICATION BY FIELD OBSERVATION HAS BEEN CONDUCTED
WHERE PRACTICAL, HOWEVER, BABCOCK, JONES AND ASSOCIATES
INC. DOES NOT GUARANTEE THE COMPLETENESS NOR ACCURACY
THEREOF.

