





Seeding Dates	Spacies	Lb./1,000 ft. <sup>2</sup>	Per Ac.
March 1 to August 15	Oats	з .	4 bushel
	Tall Fescue	1	40 lb.
	Annual Ryegrass	1	40 lb.
	Perennial Ryegrass	1	40 lb.
	Tall Fescue	1	40 lb.
	Annual Ryegrass	1	40 lb.
August 16 to November 1	Rye	3	2 bushel
	Tell Fescue	i l	40 lb.
	Annual Ryegrass	1	40 lb.
	Wheat	3	2 bushel
	Tall Fescus	1	40 lb.
	Annual Ryegrass	1	40 lb.
	Perennial Ryegrass	1	40 lb.
	Tall Fescue	1	40 lb.
	Annual Ryagrass	1	40 lb.
Vovember 1 to Spring Seeding	Use mulch only sodd	ing practices or dorma	nt condina

Erosion and Sediment Control Schedule

Ingress-Egress

A stone access drive complete with under lying geo-textile fabric (20 feet wide and 50 feet long) for ingress and egress at the site shall be installed. This drive shall be the only entrance and exit to the site.

Silt Fence

A silt fence shall be installed prior to any earthwork activities at the site in the locations shown on the site plan as well as along the front of any lot that slopes towards the street.

Temporary Seeding

Disturbed areas of the site that are to remain idle for more than thirty(30) days shall be properly seeded and straw mulched within seven(7) days of completion of intitial grading. Temporary seeding and mulching as a thirty(30) foot strip of the entire front of the lot shall be maintained on the site once initial grading is complete.

Stabilization of critical areas within fifty(50) feet of any stream or wetland shall be complete within two(2) days of the disturbance if the site is to remain inactive for longer than fourteen(14) days.

Straw-mulch shall be applied at a rate of 1 bale per every ten (10) feet of curb, at a width of thirty(30) feet to the entire length of the lot. Wood chips may also be used but must be spread at a minimum depth of four inches over the thirty-foot width and must be accompanied by a properly installed silt

<u>Maintenance</u>

Erosion and sediment controls shall be inspected every seven(7) days or within 24 hours of a 0.5" or greater rainfall event. Necessary repairs shall be made at this time.

"I, the undersigned hereby certify that this topography indicated by 6", 1', or 2' contours, and elevations shown hereon represent an actual field survey made by me on the day of,2006 and that the elevations were taken at appropriate intervals and that as of that date they existed as indicated hereon."

PANESULVE TWP. LAKE COUNTY, OHIO OWNER ADDRESS STREET ZIP CITY AKE EMESHARES TRACT SUBDIVISION STREET LOT 279 VOL.-PG. SUBLOT NO. STREET VOL-PG. PERM. PARCEL NO. LEGEND EXIST. ELEV. 5 100.0 22 PROP. ELEV. SANITARY MANHOLE ----STORM MANHOLE ----AS BUILT ELEVATION INLET OR CATCH BASIN DIRECTION OF EXISTING CONTOURS SURFACE DRAINAGE PROPOSED CONTOURS REMARKS ALL BOUNDARY DATA SHOWN WAS OBTAINED FROM (DEEDS, RECORDED SUBDIVISION PLAT OR OTHER PUBLIC RECORDS) LOCATIONS AS SHOWN OF ADJACENT WELLS AND SEPTIC TANKS OBTAINED FROM LAKE COUNTY HEALTH DEPARTMENT DESIGN CERTIFICATION THIS PLAT WAS PREPARED BY ME, AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF. #6343 SURVEYOR REGISTRATION NO. NAME / NO. OF BEDROOMS WATER MAIN SIZE, LOCATION SAN, SEVIER SIZE IS GR. LOC. SAN, MH. CAST. ELEV. INV. ELEV. SAN, CONN. SIZE, LOC. DEPTH DIMENSIONS BEARINGS TIE TO NEAREST STREET SUBLOT NO. PARCEL NO. STORM SEVIER SIZE % GR. LOC. SURROUNDING OVINERS STORM MH. CAST ELEV. INV. ELEV. BLDG. DIMENSIONS FIN GR. PAY'T TYPE GRADE CURBS BLDG. TIES FL'R. GRADES GAS LINE LOC. SIZE PRESSURE APRON TYPE WIDTH THICKNESS SEPTIC TANK LOCATION & DUPLICATION AREA SIDEWALK TYPE WIDTH THICKNESS CULVERT TYPE DIA., LENGTH ISOLATION RADIUS FROM WELL **ROCK OUTCROPPINGS** REVISIONS PLAN PREPARED BY: NO. DATE 1

BABCOCK · JONES & ASSOCIATES, INC. PAINESVILLE, OHIO 2 IONE NO. 440-357-1811 3 DRAVING NO. 4 1/12/06

"AS BUILT" CERTIFICATION I, HEREBY CERTIFY THAT THE CIRCLED GRADES ARE EXISTING FINISH GRADES CHECKED IN THE FIELD ON \_\_\_\_\_\_\_, 20\_\_\_\_\_ AND ARE CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED SURVEYOR

THEREOF.

REG. NO.

EXISTING UTILITIES NOTE: THE SIZE AND LOCATION, BOTH HORIZONTAL AND VERTICAL OF THE UNDERGROUND UTILITIES SHOWN HEREON, HAVE BEEN HARRY S. JONES, JR. OBTAINED BY A SEARCH OF AVAILABLE RECORDS. VERIFICATION BY FIELD OBSERVATION HAS BEEN CONDUCTED 8-6343 WHERE PRACTICAL, HOWEVER, BABCOCK, JONES AND ASSOCIATES INC. DOES NOT GUARANTEE THE COMPLETENESS NOR ACCURACY

