





Oats	3 ·	4 bushel
Tall Fescue	1	40 lb.
Annual Ryegrass	1	40 lb.
Perennial Ryegrass Tall Fescue Annual Ryegrass	1 1 1	40 lb. 40 lb. 40 lb.
Rye	3	2 bushel
Tall Fescue	1	40 lb.
Annual Ryegrass	1	40 lb.
Wheat	3	2 bushei
Tail Fescue	1	40 lb.
Annual Ryegrass	1	40 lb.
Perennial Ryegrass	1	40 lb.
Tall Fescue	1	40 lb.
Annual Ryegrass	1	40 lb.
	Tall Fescue Annual Ryegrass Perennial Ryegrass Tall Fescue Annual Ryegrass Rye Tall Fescue Annual Ryegrass Wheat Tall Fescue Annual Ryegrass Perennial Ryegrass Tall Fescue	Tall Fescue 1 Annual Ryegrass 1 Perennial Ryegrass 1 Tall Fescue 1 Annual Ryegrass 1 Rye 3 Tall Fescue 1 Annual Ryegrass 1 Wheat 3 Tall Fescue 1 Annual Ryegrass 1 Perennial Ryegrass 1 Perennial Ryegrass 1 Tall Fescue 1 Annual Ryegrass 1

Erosion and Sediment Control Schedule

Ingress-Egress

A stone access drive complete with under lying geo-textile fabric (20 feet wide and 50 feet long) for ingress and egress at the site shall be installed. This drive shall be the only entrance and exit to the site.

Silt Fence
A silt fence shall be installed prior to any earthwork activities at the site in the locations shown on the site plan as well as along the front of any lot that slopes towards the street.

Temporary Seeding
Disturbed areas of the site that are to remain idle for more than thirty(30) days shall be properly seeded and straw mulched within seven(7) days of completion of intitial grading. Temporary seeding and mulching as a thirty(30) foot strip of the entire front of the lot shall be maintained on the site once initial grading is complete.

Stabilization of critical areas within fifty(50) feet of any stream or wetland shall be complete within two(2) days of the disturbance if the site is to remain inactive for longer than fourteen(14) days.

Mulching Straw—mulch shall be applied at a rate of 1 bale per every ten (10) feet of curb, at a width of thirty(30) feet to the entire length of the lot. Wood chips may also be used but must be spread at a minimum depth of four inches over the thirty—foot width and must be accompanied by a properly installed silt fence.

Maintenance

Erosion and sediment controls shall be inspected every seven(7) days or within 24 hours of a 0.5" or greater rainfall event. Necessary repairs shall be made at this time.

> "I. the undersigned hereby certify that this topography indicated by 6", 1', or 2' contours, and elevations shown hereon represent an actual field survey made by me on the 200 day of April, 2004 and that the elevations were taken at appropriate intervals and that as of that date they existed as indicated hereon."

Reg. No.

	PAINEVILLE TWO.	LAKE COUNTY, OHIO		
ļ	for: KAY HOMES	OWNER		
	ADDRESS S	TREET CITY ZIP		
	LAKE ERIESHARES =2	TDAGT		
	SUBDIVISION 45-30 NAME	TRACT STREET		
ļ	SUBLOT NO. STREET VOLPG. PERM. PARCEL NO.			
	LEGEND			
	SANITARY MANIHOLE ————	EXIST. ELEV. 100.0 2 PROP. ELEV.		
	STORM MANHOLE	AS BUILT ELEVATION		
	INLET OR CATCH BASIN	5 INDICATES		
	EXISTING CONTOURS	S DIRECTION OF		
	PROPOSED CONTOURS	SURFACE DRAINAGE		
	REMARKS ALL BOUNDARY DATA SHOWN WAS OBTAINED FROM (DEEDS, RECORDED SUBDIMISION PLAT OR OTHER PUBLIC RECORDS)			
	LOCATIONS AS SHOWN OF ADJACENT WELLS AND SEPTIC TANKS OBTAINED FROM LAKE COUNTY HEALTH DEPARTMENT			
	DESIGN CERTIFICATION			
	THIS PLAT WAS PREPARED BY ME, AND IS CORRECT			
	TO THE BEST OF MY KNOWLEDGE AND BELIEF.			
	NAME SI	REGISTRATION NO.		
	(CHECK LIST			
	NO. OF BEDROOMS DIMENSIONS	WATER MAIN SIZE, LOCATION SAN, SEWER SIZE % GR. LOC.		
	BEARINGS TIE TO NEAREST STREET	SAN. MH. CAST. ELEV. INV. ELEV. SAN. CONN. SIZE, LOC. DEPTH		
	SUBLOT NO. PARCEL NO. SURROUNDING OWNERS	STORM SEWER SIZE % GR. LOC. STORM MH. CAST ELEV. INV. ELEV.		
	BLDG, DIMENSIONS FIN GR. BLDG, TIES FL'R, GRADES	PAY'T TYPE GRADE CURBS GAS LINE LOC. SIZE PRESSURE		
	APRON TYPE WIDTH THICKNESS SIDEWALK TYPE WIDTH THICKNESS CULVERT TYPE DIA., LENGTH	SEPTIC TANK LOCATION & DUPLICATION AREA WELL LOCATION ISOLATION RADIUS FROM WELL.		
	ROCK OUTCROPPINGS REVISIONS			
	NO DATE BY	PLAN PREPARED BY:		

DÍ BABCOCK · JONES & ASSOCIATES, INC. IONE NO. 440-357-1811 03-234-169

"AS BUILT" CERTIFICATION

I, HEREBY CERTIFY THAT THE CIRCLED GRADES ARE EXISTING
FINISH GRADES CHECKED IN THE FIELD ON ________, 20_____
AND ARE CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED SURVEYOR

EXISTING UTILITIES NOTE:
THE SIZE AND LOCATION, BOTH HORIZONTAL AND VERTICAL
OF THE UNDERGROUND UTILITIES SHOWN HEREON, HAVE BEEN OBTAINED BY A SEARCH OF AVAILABLE RECORDS. VERIFICATION BY FIELD OBSERVATION HAS BEEN CONDUCTED WHERE PRACTICAL, HOWEVER, BABCOCK, JONES AND ASSOCIATES INC. DOES NOT GUARANTEE THE COMPLETENESS NOR ACCURACY THEREOF.

