





Seeding Dates	Species	Lb./1,000 ft. ²	Per Ac.
March 1 to August 15	Oats Tall Fescue Annual Ryagrass	3 - 1 1	4 bushel 40 lb. 40 lb.
	Perennial Ryegrass Tall Fescue Annual Ryegraes	1 1 1	40 lb. 40 lb. 40 lb.
August 16 to November 1	Rye Tall Fescue Annual Ryegrass	3 1 1	2 bushel 40 lb. 40 lb.
	Wheat Tall Fescue Annual Ryegrass	3 1 1	2 bushel 40 lb. 40 lb.
	Perennial Ryegrass Tall Fescue Annual Ryegrass	1 1 1	40 lb. 40 lb. 40 lb.

Erosion and Sediment Control Schedule

Ingress-Egress

A stone access drive complete with under lying geo-textile fabric (20 feet wide and 50 feet long) for ingress and egress at the site shall be installed. This drive shall be the only entrance and exit to the site.

Silt Fence A silt fence shall be installed prior to any earthwork activities at the site in the locations shown on the site plan as well as along the front of any lot that slopes towards the street.

Temporary Seeding
Disturbed areas of the site that are to remain idle for more than thirty(30) days shall be properly seeded and straw mulched within seven(7) days of completion of intitial grading. Temporary seeding and mulching ao a thirty(30) foot strip of the entire front of the lot shall be maintained on the site once initial grading is complete.

Stabilization of critical areas within fifty(50) feet of any stream or wetland shall be complete within two(2) days of the disturbance if the site is to remain inactive for longer than fourteen(14) days.

Straw-mulch shall be applied at a rate of 1 bale per every ten (10) feet of curb, at a width of thirty(30) feet to the entire length of the lot. Wood chips may also be used but must be spread at a minimum depth of four inches over the thirty-foot width and must be accompanied by a properly installed silt fence.

Erosion and sediment controls shall be inspected every seven(7) days or within 24 hours of a 0.5" or greater rainfall event. Necessary repairs shall be made at this time.

> "I, the undersigned hereby certify that this topography indicated by 6", 1', or 2' contours, and elevations shown hereon appropriate intervals and that as of that date they existed as indicated hereon."

2					
	PAINTESULLE TWP, LAKE COUNTY, OHIO				
	FOR: KNEZ CONSTRUCTION OWNER				
	ADDRESS ST	ADDRESS STREET CITY ZIP			
	LAICE ERIESHORES +2	TRACT			
	SUBDIVISION 45-30 NAME 1/3 VOL-PO. PED BLE BEACH COVE STREET				
	SUBLOT NO. STREET		M. PARCEL NO.		
	STORM MANHOLE	AS BUILT ELEVATION INDICATES	PROP. ELEV.		
	EXISTING CONTOURS ———— PROPOSED CONTOURS ————	DIRECTION OF SURFACE DRAINAGE	E		
	REMARKS ALL BOUNDARY DATA SHOWN WAS OBTAINED FROM (DEEDS, RECORDED SUBDIVISION PLAT OR OTHER PUBLIC RECORDS) LOCATIONS AS SHOWN OF ADJACENT WELLS AND SEPTIC TANKS OBTAINED FROM LAKE COUNTY HEALTH DEPARTMENT DESIGN CERTIFICATION THIS PLAT WAS PREPARED BY ME, AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF. TO THE BEST OF MY KNOWLEDGE AND BELIEF. SURVEYOR REGISTRATION NO.				
,					
	/ CHECK LIST				
	O. OF BEDROOMS IMENSIONS EARINGS IE TO NEAREST STREET UBLOT NO. PARCEL NO. URROUNDING OWNERS LDG. DIMENSIONS FIN GR. LDG. TIES FL'R. GRADES PRON TYPE WIDTH THICKNESS IDEWALK TYPE WIDTH THICKNESS ULVERT TYPE DIA., LENGTH OCK OUTCROPPINGS WATER MAIN SIZE, LOCATION SAN. SEWER SIZE % GR. LOC. SAN. MH. CAST. ELEV. INV. ELEV. SAN. CONN. SIZE, LOC. DEPTH STORM SEWER SIZE % GR. LOC. STORM MH. CAST ELEV. INV. ELEV. PAV'T TYPE GRADE CUTGES GAS LINE LOC. SIZE PRESSURE SEPTIC TANK LOCATION & DUPLICATION AR WELL LOCATION ISOLATION RADIUS FROM WELL				
	REVISIONS	DI ANI DOCDADED EM			

PLAN PREPARED BY: BABCOCK · JONES & ASSOCIATES, INC. PAINESVILLE, OHIO 2 ONE NO. 440—357—1811 03-234-113

AND ARE CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED SURVEYOR

REG. NO.

EXISTING UTILITIES NOTE:
THE SIZE AND LOCATION, BOTH HORIZONTAL AND VERTICAL
OF THE UNDERGROUND UTILITIES SHOWN HEREON, HAVE BEEN
OBTAINED BY A SEARCH OF AVAILABLE RECORDS.
VERIFICATION BY FIELD OBSERVATION HAS BEEN CONDUCTED
WHERE PRACTICAL, HOWEVER, BABCOCK, JONES AND ASSOCIATES
INC. DOES NOT GUARANTEE THE COMPLETENESS NOR ACCURACY

