





Seeding Dates	Species	Lb./1,000 ft. ²	Par Ad.
March 1 to August 15	Oats	3 -	4 bushel
	Tall Fescue	1	40 lb.
	Annual flyegrass	1	40 lb.
	Perennial Ryegrass	7	40 lb.
	Tell Fescue	1	40 lb.
	Annual Ryegrass	1	40 lb.
August 16 to November 1	Rye	3	2 bushel
	Tall Fescue	1	40 lb.
	Annual Ryegrass	1	40 ib.
	Wheat	3	2 bushel
	Tall Fescue	1	40 lb.
	Annual Ryegrass	1	40 lb.
	Parennial Ryegrass	. 1	40 lb.
	Tall Fescue	1	40 lb.
	Annual Ryegrass	1	40 lb.

Erosion and Sediment Control Schedule

Ingress-Egress

A stone access drive complete with under lying geo-textile fabric (20 feet wide and 50 feet long) for ingress and egress at the site shall be installed. This drive shall be the only entrance and exit to the site.

Silt Fence

A silt fence shall be installed prior to any earthwork activities at the site in the locations shown on the site plan as well as along the front of any lot that slopes towards the street.

Temporary Seeding
Disturbed areas of the site that are to remain idle for more than twenty one(21) days shall be properly seeded and straw mulched within seven(7) days of completion of intitial grading. Temporary seeding and mulching as a thirty(30) foot strip of the entire front of the lot shall be maintained on the site once. initial grading is complete.

Stabilization of critical areas within fifty(50) feet of any stream or wetland shall be complete within two(2) days of the disturbance if the site is to remain inactive for longer than fourteen(14) days.

Straw-mulch shall be applied at a rate of 1 bale per every ten (10) feet of curb, at a width of thirty(30) feet to the entire length of the lot. Wood chips may also be used but must be spread at a minimum depth of four inches over the thirty-foot width and must be accompanied by a properly installed silt fence.

Maintenance

Erosion and sediment controls shall be inspected every seven(7) days or within 24 hours of a 0.5" or greater rainfall event. Necessary repairs shall be made at this time.

> "I, the undersigned hereby certify that this topography indicated by 6", 1', or 2' contours, and elevations shown hereon represent an actual field survey made by me on the ______ day o _______,20// and that the elevations were taken at appropriate intervals and that as of that date they existed as indicated hereon.'

				·						
2										
	PORRY TO	PERRY TOWNSHIP, LAKE COUNTY, OHIO								
	for: MARY	MARY PATRIACEA								
	/	CLIENT OWNER								
	ADDRESS	SIRI	ET.	CITY	ZIP					
	AZALBA GO	NAME NAME	TRA	a						
	SUBDIVISION 24-3 VOL-9	in moliner	() ₍ TO	T	STREET 3A - TSA-25					
	SUBLOT NO.	STREET	VO	PG	PERM. PARCEL NO.					
		LEGE		- Certon o						
	SANITARY MANHOLE	0	exist. ele	v.— = 100.0	PROP. ELEV.					
	STORM MANHOLE		AS BUILT I	ELEVATION	(39.3)					
	INLET OR CATCH BASIN -		ک	INDICATES						
	EXISTING CONTOURS -	MANAGE CONTROL AND ADDRESS OF THE PARTY OF T	3	DIRECTION C SURFACE DE						
	PROPOSED CONTOURS —		<u> </u>							
	ALL BOUNDARY DATA	REMAI		u (neene e	FCORDED					
	SUBDIVISION PLAT OF	OTHER PUBLIC RE	CORDS)	to frammas .	LOONULU					
	LOCATIONS AS SHOW	N OF ADJACENT WE	LLS AND	SEPTIC TANK	KS OBTAINED FROM					
	LAKE COUNTY HEALTH	1 DEPARIMENT								
	DESIGN CERTIFICATION									
,	THIS PLAT/	THIS PLAT WAS PREPARED BY ME, AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.								
	10 THE BES		LEUGE	1634	3					
	NAME V	รซ์หัง	EYOR	REGIST	RATION NO.					
	CHECK LIST									
	NO. OF BEDROOMS DIMENSIONS		SAN. SEWI	IN SIZE, LOCA ER SIZE % GR.	LOC.					
	BEARINGS THE TO NEAREST STREET SUBLOT NO. PARCEL NO.	# ·	SAN. CON	CAST. ELEV. IN N. SIZE, LOC.	DEPTH					
	SURROUNDING OWNERS BLDG. DIMENSIONS FIN GR	,	STORM MI	WER SIZE % G 1. CAST ELEV.	INV. ELEV.					
. 124	BLDG. TIES FL'R. GRADES APRON TYPE WIDTH THICK		GAS LINE	E GRADE CURE LOC: SIZE PRE	SSURE					
	SIDEWALK TYPE WIDTH THI CULVERT TYPE DIA., LENG	CKNESS [WELL LOC	ATION	& DUPLICATION AREA					
	ROCK OUTCROPPINGS									
	REVISIONS NO. DATE BY		PLAN	PREPARED BY	ń					
	1	BABCOCK	K · JON	ES & ASS	SOCIATES, INC.					
			PAIN	ESVILLE, OHIO						
	3	DRAWN BY	SCALE		PHONE NO. 440-357-1811					
	4	снко.	DATE	0/20111	RAWING NO.					
	5	CREW CHIEF	APP'D	HE TO	06-147-25					
	- Mariana - Mari	A STATE OF THE STA		· · · · · · · · · · · · · · · · · · ·						

"AS BUILT" CERTIFICATION I, HEREBY CERTIFY THAT THE CIRCLED GRADES ARE EXISTING FINISH GRADES CHECKED IN THE FIELD ON ______, 20____ AND ARE CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

registered surveyor

EXISTING UTILITIES NOTE:
THE SIZE AND LOCATION, BOTH HORIZONTAL AND VERTICAL OF THE UNDERGROUND UTILITIES SHOWN HEREON, HAVE BEEN HARRY S. JONES, JR. OF THE ONDERGOOD OF THE TEST SHOWN TERESON, TAVE SEEN OBTAINED BY A SEARCH OF AVAILABLE RECORDS.

VERIFICATION BY FIELD OBSERVATION HAS BEEN CONDUCTED WHERE PRACTICAL, HOWEVER, BABCOCK, JONES AND ASSOCIATES INC. DOES NOT GUARANTEE THE COMPLETENESS NOR ACCURACY 5-6343