

LINE	BEARING	DISTANCE
L1	N 00°51'07" E	60.00'
L2	N 00°51'07" E	40.10'
L3	S 89°22'14" E	16.50'
L4	S 00°51'07" W	40.16'
L5	N 89°08'53" W	16.50'
L6	S 00°51'07" W	60.00'
L7	S 89°22'14" E	8.25'
L8	S 00°51'07" W	10.16'
L9	N 89°08'53" W	8.25'
L10	N 00°51'07" E	10.13'
L11	S 88°56'16" E	16.50'
L12	S 00°51'07" W	85.00'
L13	N 89°22'14" W	8.25'
L14	S 00°51'07" W	75.00'
L15	S 89°22'14" E	8.25'
L16	N 89°08'53" W	16.50'

LINE	BEARING	DISTANCE
L17	N 00°51'07" E	60.00'
L18	N 00°51'07" E	25.13'
L19	N 89°08'53" W	8.25'
L20	S 00°51'07" W	34.84'
L21	N 89°22'14" W	8.25'

**TITLE:**  
 Situated in the City of Mentor, County of Lake and State of Ohio and known as being part of Lot No. 7, Tract No. 13 and being part of a 16.5 foot wide strip of land along the east line of Thistlewood Acres Subdivision No. 3

**Barrington**  
 CONSULTING GROUP, INC.  
 Bearings used herein are to denote angular relationship only and do not represent true north.

**GRAPHIC SCALE**




(IN FEET)  
 1 inch = 60 ft.

**CERTIFICATION:**

THIS BOUNDARY SURVEY REPRESENTS THE MINIMUM STANDARDS FOR BOUNDARY SURVEYS IN THE STATE OF OHIO AS ADOPTED MAY 1st, 1980 OF THE OHIO REVISED CODE CHAPTER 4733-37. SURVEYED ON THE 3rd DAY OF JUNE, 2002. UNDER THE SUPERVISION OF DAVID W. NOVAK, P.S. No. 7507. ALL PIN SET ARE 5/8" DIA., 30" LONG REBAR WITH CAP MARKED "NOVAK 7507". ALL PROPERTY CORNERS WERE EITHER SET OR FOUND AS INDICATED.

"I HEREBY CERTIFY THAT THIS PLAN WAS PREPARED BY ME AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF"

DAVID W. NOVAK, P.S. No. 7507



REVISIONS	BY

**Barrington**  
 CONSULTING GROUP, INC.  
 38342 WESTERN PARKWAY, SUITE 10  
 WILLOUGHBY, OHIO 44094  
 PHONE 440-946-1761 FAX 440-918-0486



**LOT SPLIT**  
 6167 BRAMBLEWOOD PLACE  
 MENTOR, OHIO 44060  
 THOMAS ROBINSON

DRAWN  
 CHECKED  
 DWN  
 DATE  
 JUNE 26, 2002  
 SCALE  
 1" = 60'  
 JOB NO.  
 02059A  
 SHEET  
 11  
 OF SHEETS