



STORM SEWERS				
Location		Side	I-8 M.H. Adjust. to Grade	I-16 C.B. Abandon
From	To		Each	Each
0+50	9+74	L	3	4

UNDERDRAINS				
Location		Side	I-4 6" Under drain	
From	To		Lin. Ft.	
0+00	10+00	L	996	

PAVEMENT QUANTITIES								
STATIONS		3-709" PORTLAND CEMENT CONC. BASE COURSE	I-22 6" SUBBASE	I-18 6" STABILIZED CRUSHED AGGREGATE SHOULDER	E-8 REMOVAL & DISPOSAL OF EXIST. PAVT.	T-35 1 1/4" ASPHALTIC CONCRETE SURFACE COURSE	3-35 1/4" MIN. ASPHALTIC CONCRETE LEVELING COURSE	T-30 BITUMIN. TACK COAT
FROM	TO	SQ. YDS.	CU. YDS.	CU. YDS.	SQ. YDS.	CU. YD.	CU. YD.	GAL.
0+00	10+00	1172	219	123	5	141	160*	406

\* INCLUDES EXTRA LEVELING:  
100 CU. YD./MILE x 0.189 MI. = 19 CU. YD.

WATER MAIN	
VALVE BOX ADJUSTED TO GRADE	9 EA.
MANHOLE CASTING ADJUSTED TO GRADE	1 EA.
TEE PLUGGED AT MAIN	3 EA.
HYDRANT REMOVED AND DISPOSED	2 EA.
8" WATER LINE REMOVED	300 L.F.

PLAN & PROFILE... EXISTING LAKEWOOD BLVD. STA. 0+00 TO STA. 10+00