

R-44R
R-44L



	O	N	E	TOTAL		
5"D	3.50	1.18	3.36	1.47	3.05	12 ⁹ / ₁₆
7"C	4.05	1.39	3.83	1.74	3.50	14 ¹ / ₂
	W	A	Y	TOTAL		
5"D	4.38	.50	4.19	.14	4.22	13 ⁷ / ₁₆
7"C	5.25	.56	4.38	-.18	4.38	14 ¹ / ₁₆

CODE NUMBER	VALUES																				
	A	B	C	D	E	F	G	H	J	K	L	M	N	O	P	Q	R	R ₁	R ₂	MARGIN	BORDER
R-44R-18 R-44L-18	18	24	6 ¹ / ₄	6 ⁵ / ₁₆	6 ⁵ / ₈	6 ¹³ / ₁₆	4 ¹ / ₂	6 ¹ / ₄	5 ³ / ₄	3	5"D	2	2 ¹ / ₂	4 ⁷ / ₈	2	7 ⁷ / ₈	1 ¹ / ₂	1 ¹ / ₄	3 ³ / ₈	3 ³ / ₈	3 ³ / ₈
R-44R-24 R-44L-24	24	30	7 ¹ / ₄	7 ¹ / ₄	6 ⁷ / ₈	7 ³ / ₁₆	5 ¹ / ₂	8 ⁷ / ₈	8 ⁷ / ₈	3	7"C	1 ³ / ₄	3 ¹ / ₄	6 ¹ / ₄	2 ¹ / ₈	13 ¹³ / ₁₆	1 ¹ / ₂	5 ⁵ / ₁₆	1 ¹ / ₂	1 ¹ / ₂	1 ¹ / ₂

NOTES:
 ROTATE GIVEN DESIGN 180° ABOUT VERTICAL PLATE Q-Q FOR PLACEMENT OF LEFT ARROW.
 ARROW IS SYMMETRICAL ABOUT ARROW AXIS (Z-Z).
 ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SHOWN.

BUREAU OF TRAFFIC OHIO DEPARTMENT OF HIGHWAYS		<table border="1"> <tr> <td>R-44R</td> <td rowspan="2">DATE 12-23-64 3-1-66</td> </tr> <tr> <td>R-44L</td> </tr> </table>	R-44R	DATE 12-23-64 3-1-66	R-44L
R-44R	DATE 12-23-64 3-1-66				
R-44L					
TRAFFIC SIGNS		APPROVED _____ ENGINEER OF TRAFFIC			