

ITEM 621-REMOVAL OF PAVEMENT MARKINGS  
SUB-SUMMARY

BRIDGE	PHASE	STATIONING (FROM TO) (SIDE)	EDGE LINE		LANE LINE	CHANNELIZING LINE	RE MARKS
			RIGHT	LEFT			
			LINE AR		FEET		
LAK-2-1.80 R	I	178+60 TO 187+70 R 187+70 TO 203+90 R	1620		910 1620		
	II	183+00 TO 187+70 R 192+10 TO 195+10 R 196+70 TO 199+50 R		300 280	470 300 280		
LAK-2-1.80 L	I	187+95 TO 204+15 L 204+15 TO 213+25 L	1620		1620 910		
	II	192+35 TO 195+10 L 196+80 TO 199+50 L 196+80 TO 199+75 L		275 270	275 295		
LAK-2-3.63 R	I	273+65 TO 284+25 R 276+85 TO 284+25 R 282+20 TO 300+45 R 285+50 TO 298+70 R	740 1320		1060 1825		RAMP C-3
	II	273+10 TO 282+20 R 288+70 TO 291+60 R 288+70 TO 296+10 R 293+90 TO 296+10 R RAMP C-3 276+90 TO 279+70 L		740	910 290 220	280	
LAK-2-3.63 L	I	286+85 TO 296+80 L 286+75 TO 299+00 L 296+80 TO 300+50 L 298+00 TO 304+15 L 299+60 TO 304+15 L	1225 455		1005 615	370	
	II	289+05 TO 292+00 L 293+40 TO 296+45 L		295 305	295 305		
LAK-2-5.42	I	25+00 TO 33+60 R 26+50 TO 27+50 L 27+00 TO 27+35 R 27+00 TO 33+60 R 27+35 TO 28+85 L 31+30 TO 33+50 L 32+60 TO 36+50 L	660	35 660 150 220	860 150		SOUTHBOUND
	II	22+75 TO 24+25 R 27+00 TO 28+80 L 27+50 TO 28+80 L 31+25 TO 32+60 L 31+25 TO 33+00 L	180 175		150 130 135		
SUB-TOTALS			7995	3530			
* TOTALS			11,525		15,020	650	

ADVANCE WARNING SIGNS

BRIDGE	PHASE	DIRECTION	CHANGE	DISTANCE	SIGN	SIZE	DESCRIPTION	SIDE	
LAK 2-1.80	I	EASTBOUND & WESTBOUND	LEFT LANE CLOSURE	500'	OW-60D	48"X48"		R & L	
				1000'	OW-123MOD	48"X48"	LEFT LANE CLOSED 1000 FT.	R & L	
				1000'	OW-143	24"X24"	45 MPH	R & L	
				2000'	OW-123MOD	48"X48"	LEFT LANE CLOSED 2000 FT.	R & L	
				2000'	OW-143	24"X24"	45 MPH	R & L	
	LAK 2-3.63	II	EASTBOUND & WESTBOUND	RIGHT LANE CLOSURE	500'	OW-60C	48"X48"		R & L
					1000'	OW-122MOD	48"X48"	RIGHT LANE CLOSED 1000 FT.	R & L
					1000'	OW-143	24"X24"	45 MPH	R & L
					2000'	OW-122MOD	48"X48"	RIGHT LANE CLOSED 2000 FT.	R & L
					2000'	OW-143	24"X24"	45 MPH	R & L
LAK 2-5.42		I	EASTBOUND	LEFT LANE CLOSURE	500'	OW-60D	48"X48"		R & L
					1000'	OW-123MOD	48"X48"	LEFT LANE CLOSED 1000 FT.	R & L
					1000'	OW-143	24"X24"	45 MPH	R & L
					2000'	OW-123MOD	48"X48"	LEFT LANE CLOSED 2000 FT.	R & L
					2000'	OW-143	24"X24"	45 MPH	R & L
	II	WESTBOUND	LEFT LANE SHIFT	500'	OW-128	48"X48"	ROAD CONSTRUCTION AHEAD	R & L	
				500'	OW-143	24"X24"	35 MPH	R & L	
				1000'	OC-49R	48"X48"	RIGHT LANE MUST USE SHOULDER	R & L	
				1000'	OW-145A	30"X16"	1000 FEET	R & L	
				2000'	OW-128	48"X48"	ROAD CONSTRUCTION AHEAD	R & L	
LAK 2-3.63	II	EASTBOUND	RIGHT LANE CLOSURE	500'	OW-60C	48"X48"		R & L	
				1000'	OW-123MOD	48"X48"	RIGHT LANE CLOSED 1000 FT.	R & L	
				1000'	OW-143	24"X24"	45 MPH	R & L	
				2000'	OW-123MOD	48"X48"	RIGHT LANE CLOSED 2000 FT.	R & L	
				2000'	OW-143	24"X24"	45 MPH	R & L	
	II	WESTBOUND	LEFT LANE SHIFT	1000'	OW-128	48"X48"	ROAD CONSTRUCTION AHEAD	R & L	
				1000'	OW-143	24"X24"	45 MPH	R & L	

ITEM 202-RAISED PAVEMENT MARKERS REMOVED FOR STORAGE  
SUB-SUMMARY

BRIDGE	PHASE	STATIONING (FROM - TO) (SIDE)	INTERVAL	ONE WAY		TWO WAY			
				WHITE	YELLOW	W/R	Y/R	W/W	Y/Y
LAK-2-1.80 R	I	195+10 TO 196+70 R	80			2			
	II	195+10 TO 196+70 R	80			2			
LAK-2-1.80 L	I	195+10 TO 196+70 L	80			2			
	II	195+10 TO 196+70 L	80			2			
LAK-2-3.63 R	I	291+55 TO 293+05 R	80			2			
	II	291+55 TO 293+05 R	80			2			
LAK-2-3.63 L	I	292+10 TO 293+50 L	80			2			
	II	292+10 TO 293+50 L	80			2			
LAK-2-5.42	I	28+80 TO 31+50	40	9		9			9
	II	28+90 TO 31+60	40	9		9			9
SUB-TOTALS				18		34			18
*TOTALS						70			

THESE TOTALS HAVE BEEN TRANSFERRED TO THE GENERAL SUMMARY (SEE SHEET NO. 27.)

LAK-2-(1.80/10.29)