



NOTE "A"

FIT OF INTERMEDIATE STIFFENERS: Supplementary to Section S-7.14 of the Construction and Material Specifications intermediate stiffeners shall have contact bearing with the compression flange but may have a clearance of not more than 1/8 inch from the tension flange at the locations shown. In shop painting care shall be taken to make certain that paint is forced through from one side to the other of the 1/8 inch opening.

ALL FIELD CONNECTIONS shall be made with 7/8" high strength bolts except where field welding is shown on Plans.

NO CAMBER required.

PREPARED BY
CAPITOL ENGINEERING ASSOCIATES, DILLSBURG, PA.
FOR

STATE OF OHIO
DEPARTMENT OF HIGHWAYS
DIVISION OF DESIGN AND CONSTRUCTION
BUREAU OF BRIDGES

STEEL FRAMING PLAN
BRIDGE NO. LAK-2-1721
RELOC. S.R.2 UNDER FP & E R.R.
LAKE COUNTY
STA. 808+46.23

| | | | | | | |
|----------|------------------|--------|---------|---------|------|---------|
| DESIGNED | DRAWN | TRACED | CHECKED | REVISED | DATE | REVISED |
| B.O.L. | B.O.L. K.D.L. | J.S. | L.L.D. | | | |