



**ELEVATION TABLE**

B	641.77
C	642.06
D	642.34
E	642.63
F	642.93
G	643.16

- LEGEND**
- \* MINIMUM SLOPE OF PIPE IS 1/8 IN./FT.
  - \*\* PLACE TEMPORARY END CAP ON PERFORATED C.P.P. AT PHASE B CONSTRUCTION JOINT UNTIL PHASE C PERFORATED C.P.P. CAN BE ATTACHED IN ITS FINAL POSITION.
  - \*\*\* BAR TO BE PLACED PARALLEL TO CL CONSTRUCTION.
  - # 44°18'00"
  - \*\* COST INCLUDED WITH SUBSTRUCTURE CONCRETE FOR PAYMENT.

- NOTES**
1. FOR REMOVAL DETAILS SEE SHEETS 14/67 AND 16/67.
  2. FOR REAR ABUTMENT DETAILS SEE SHEETS 22/67 AND 23/67.
  3. MINIMUM BAR LAPS: #5 BAR = 36", #8 BAR = 69", #9 BAR = 97".
  4. FOR SECTION A-A, B-B AND VIEW F-F SEE SHEET 22/67.
  5. FOR SECTION D-D, J-J AND K-K SEE SHEET 23/67.
  6. FOR ABUTMENT DIAPHRAGM DETAILS, SEE SHEET 49/67.
  7. ELEVATIONS ARE TAKEN ALONG CENTERLINE OF BEARING.
  8. FOR A LIST OF ABBREVIATIONS, SEE SHEET 4/67.
  9. CONTRACTOR SHALL ACCURATELY LOCATE EXISTING 15' Ø CMP PRIOR TO PRE-BORING HOLES FOR PILE PLACEMENT. TYPICAL AT 13 PILE LOCATIONS.
  10. ALL PHASES REFERENCED ARE TO BE COMPLETED UNDER STAGE 3 SEQUENCE OF CONSTRUCTION, SEE MOT DRAWINGS.
  11. FOR ADDITIONAL ABUTMENT FOOTING REINFORCING DETAILS, SEE SHEET 29/67.
  12. FOR PHASE C CONSTRUCTION OF REAR ABUTMENT, SEE SHEET 20/67.
  13. FOR SOIL REINFORCING LIMITS, SEE SHEET 23/67.

J:\LAK\13486\bridge\LAK002\_0400C\sheets\02\_0400CAR004.dgn 03-JUL-2008 1:40PM lintn