

**SHEET NUMBER**

NHS = SR-2, STA 586+22.12 TO STA 612+09.32  
 NHS = SR-44, STA 233+00.00 TO STA 343+55.33  
 STP = SR-2, STA 612+09.32 TO STA 657+25.10  
 NHS = SR-44, STA 31+66.10 TO STA 164+34.08

| SHEET NUMBER |     |     |      |    |       |       |       |      |     | ITEM  | ITEM EXT. | GRAND TOTAL | UNIT   | DESCRIPTION | SEE SHEET NO. |
|--------------|-----|-----|------|----|-------|-------|-------|------|-----|-------|-----------|-------------|--|-------------|---------------|
| 29           | 30  | 50P | 63   | 64 | 65    | 82    | NHS   | STP  |     |       |           |             |  |             |               |
|              |     |     | 218  |    |       |       | 196   | 22   | 620 | 10300 | 218       | EACH        | DELINEATOR, TYPE C, POST MOUNTED                                     |             |               |
|              |     |     | 150  |    |       |       | 128   | 22   | 620 | 15300 | 150       | EACH        | DELINEATOR, TYPE D, POST MOUNTED                                     |             |               |
|              |     |     | 683  |    |       |       | 592   | 91   | 621 | 00200 | 683       | EACH        | RAISED PAVEMENT MARKER, INSTALLATION ONLY                            | 63          |               |
|              |     |     | 12   |    |       |       | 12    |      | 621 | 00301 | 12        | EACH        | PRISMATIC RETROREFLECTOR, AS PER PLAN                                | 63          |               |
|              |     |     |      |    |       |       | 1     |      | 625 | 00500 | 1         | EACH        | CONNECTOR KIT, TYPE II   |             |               |
|              |     |     |      |    |       |       | 1     |      | 625 | 00600 | 1         | EACH        | CONNECTOR KIT, TYPE III  |             |               |
|              |     |     |      |    |       |       | 1     |      | 625 | 18200 | 1         | EACH        | BRACKET ARM, 15'   |             |               |
|              |     |     |      |    |       | 100   | 100   |      | 625 | 23400 | 100       | LIN.FT.     | NO. 10 AWG POLE AND BRACKET CABLE                                    |             |               |
|              |     |     |      |    |       |       | 1     |      | 625 | 26250 | 1         | EACH        | LUMINAIRE, CONVENTIONAL, 200 W, HPS, TYPE II, 480 V                  |             |               |
|              |     |     |      |    |       |       | 1     |      | 625 | 32000 | 1         | EACH        | GROUND ROD   |             |               |
| 286          | 102 |     |      |    |       |       | 370   | 18   | 626 | 00100 | 388       | EACH        | BARRIER REFLECTOR, TYPE A  |             |               |
| 4            | 7   |     |      |    |       |       | 9     | 2    | 626 | 00200 | 11        | EACH        | BARRIER REFLECTOR, TYPE B  |             |               |
|              |     |     |      |    |       | 611   | 520   | 91   | 630 | 03100 | 611       | LIN.FT.     | GROUND MOUNTED SUPPORT, NO. 3 POST                                   |             |               |
|              |     |     |      |    |       | 131   | 131   |      | 630 | 06400 | 131       | LIN.FT.     | GROUND MOUNTED SUPPORT, S4X7.7 BEAM                                  |             |               |
|              |     |     |      |    |       | 183   | 144.5 | 38.5 | 630 | 06500 | 183       | LIN.FT.     | GROUND MOUNTED SUPPORT, W6X9 BEAM                                    |             |               |
|              |     |     |      |    |       | 60.5  | 60.5  |      | 630 | 08000 | 60.5      | LIN.FT.     | GROUND MOUNTED SUPPORT, W12X30 BEAM                                  |             |               |
|              |     |     |      |    |       | 15    | 15    |      | 630 | 08004 | 15        | LIN.FT.     | ONE WAY SUPPORT, NO. 3 POST  |             |               |
|              |     |     |      |    |       | 18    | 16    | 2    | 630 | 09000 | 18        | EACH        | BREAKAWAY BEAM CONNECTION  |             |               |
|              |     |     |      |    |       | 1     | 1     |      | 630 | 25500 | 1         | EACH        | COMBINATION OVERHEAD SIGN SUPPORT, TYPE TC-12.30, DESIGN 5, 20' ARMS |             |               |
|              |     |     |      |    |       | 83.5  | 65.5  | 18   | 630 | 80102 | 83.5      | SQ. FT.     | SIGN, FLAT SHEET, TYPE G   |             |               |
|              |     |     |      |    |       | 498   | 498   |      | 630 | 80204 | 498       | SQ. FT.     | SIGN EXTRUSHEET, TYPE G  |             |               |
|              |     |     |      |    |       | 20    | 18    | 2    | 630 | 84500 | 20        | EACH        | GROUND MOUNTED BEAM SUPPORT FOUNDATION                               |             |               |
|              |     |     |      |    |       | 1     | 1     |      | 630 | 84510 | 1         | EACH        | RIGID OVERHEAD SIGN SUPPORT FOUNDATION                               |             |               |
|              |     |     |      |    |       | 12    | 10    | 2    | 630 | 84900 | 12        | EACH        | REMOVAL OF GROUND MOUNTED SIGN AND DISPOSAL                          |             |               |
|              |     |     |      |    |       | 51    | 45    | 6    | 630 | 85100 | 51        | EACH        | REMOVAL OF GROUND MOUNTED SIGN AND REERECTION                        |             |               |
|              |     |     |      |    |       | 67    | 56    | 11   | 630 | 86002 | 67        | EACH        | REMOVAL OF GROUND MOUNTED POST SUPPORT AND DISPOSAL                  |             |               |
|              |     |     |      |    |       | 2     | 2     |      | 630 | 86102 | 2         | EACH        | REMOVAL OF GROUND MOUNTED BEAM SUPPORT AND DISPOSAL                  |             |               |
|              |     |     |      |    |       | 1     | 1     |      | 630 | 89702 | 1         | EACH        | REMOVAL OF OVERHEAD SIGN SUPPORT AND DISPOSAL                        |             |               |
|              |     |     |      |    |       | 1     | 1     |      | 631 | 84000 | 1         | EACH        | SIGN SERVICE   |             |               |
|              |     |     |      |    |       | 1     | 1     |      | 631 | 84300 | 1         | EACH        | SIGN WIRED   |             |               |
|              |     |     |      |    |       | 1     | 1     |      | 631 | 85100 | 1         | EACH        | DISCONNECT SWITCH WITH ENCLOSURE, TYPE X                             |             |               |
|              |     |     |      |    |       | 2     | 2     |      | 631 | 87154 | 2         | EACH        | BALLAST TYPE CMRI-175-120, INTEGRAL                                  |             |               |
|              |     |     |      |    |       | 2     | 2     |      | 631 | 89200 | 2         | EACH        | MERCURY VAPOR LUMINAIRE, TYPE TC-31.21 WITH 175 WATT LAMP            |             |               |
|              |     |     | 5    |    |       |       | 5     |      | 632 | 26501 | 5         | EACH        | DETECTOR LOOP, AS PER PLAN   | 63          |               |
|              |     |     | 710  |    |       |       | 710   |      | 642 | 30000 | 710       | LIN.FT.     | REMOVAL OF PAVEMENT MARKING  |             |               |
|              |     |     | 0.22 |    | 15.34 | 12.56 | 24.64 | 3.48 | 828 | 10000 | 28.12     | MILE        | EDGE LINE  |             |               |
|              |     |     | 0.08 |    | 6.06  | 5.82  | 10.14 | 1.82 | 828 | 10100 | 11.96     | MILE        | LANE LINE  |             |               |
|              |     |     | 0.09 |    |       |       | 0.09  |      | 828 | 10200 | 0.09      | MILE        | CENTER LINE  |             |               |
|              |     |     | 609  |    | 2211  | 1946  | 4446  | 320  | 828 | 10300 | 4766      | LIN.FT.     | CHANNELIZING LINE  |             |               |
|              |     |     | 114  |    |       | 340   | 454   |      | 828 | 10400 | 454       | LIN.FT.     | STOP LINE  |             |               |
|              |     |     |      |    |       | 100   | 100   |      | 828 | 10500 | 100       | LIN.FT.     | CROSSWALK LINE   |             |               |
|              |     |     | 85   |    | 635   | 376   | 911   | 185  | 828 | 10600 | 1096      | LIN.FT.     | TRANSVERSE LINE  |             |               |
|              |     |     | 837  |    |       |       | 837   |      | 828 | 10800 | 837       | SQ.FT.      | ISLAND MARKING   |             |               |
|              |     |     | 15   |    |       | 10    | 25    |      | 828 | 20300 | 25        | EACH        | LANE ARROW   |             |               |
|              |     |     | 8    |    |       | 5     | 13    |      | 828 | 20400 | 13        | EACH        | WORD "ONLY" ON PAVEMENT, 72"   |             |               |

**TRAFFIC CONTROL GENERAL SUMMARY**

**LAKE COUNTY  
LAK-2/44-13.05/4.14**

PLOTTED FROM: I:\PROJECTS\18391\18391.dgn\18391.tbl.dgn