

**GEOLOGY OF THE SITE**

THE STRUCTURE SITE IS LOCATED ON THE GLACIATED, MODERATELY DISSECTED MISSISSIPPI VALLEY PLAIN, IN AN AREA WHERE SHALLOW GLACIAL-DERIVED SOILS OVERLIE SHALE BEDROCK, OF MISSISSIPPIAN AGE.

**EXPLORATION**

THE EXPLORATION CONSISTED OF FIVE DRIVE SAMPLE-CORE BORINGS AND NINE DRIVE ROD PENETRATION TESTS, MADE BETWEEN FEBRUARY 16 AND MARCH 24, 1972.

**INVESTIGATIONAL FINDINGS**

BORINGS DISCLOSED LOOSE AND MEDIUM-DENSE SILTS AND GRAVELS AND MEDIUM-DENSE CLAY, OVERLYING GENTLY SLOPING BEDROCK SURFACE, ENCOUNTERED AT 20 TO 27-FOOT DEPTHS, ELEVATIONS 750 AND 745 FEET. THE BORINGS WERE TERMINATED AT 35 TO 55-FOOT DEPTHS, ELEVATIONS 735 TO 718 FEET, AFTER PENETRATING 13 TO 30 FEET BELOW BEDROCK SURFACE.









THE ROD SOUNDINGS ENCOUNTERED RAPID INCREASE IN PENETRATION RESISTANCE WITH INCREASE IN DEPTH, AND WERE TERMINATED DUE TO RATHER ABRUPT REFUSAL TO PENETRATION AT 19 TO 27-FOOT DEPTHS, ELEVATIONS 749 TO 746 FEET, CONSIDERED TO BE ON OR SLIGHTLY ABOVE BEDROCK SURFACE, AS REVEALED BY THE BORINGS.


NO FREE WATER OBSERVATIONS WERE MADE IN ANY OF THE ROD SOUNDING HOLES.


IF IT IS THE INTENTION TO FOUND SUBSTRUCTURE UNITS ON BEDROCK, IT IS CONSIDERED ADVISABLE THAT THE OPEN EXCAVATIONS BE INSPECTED IN THE FIELD, IN ORDER TO INSURE THAT THE EXCAVATIONS HAVE BEEN EXTENDED TO ROCK THROUGHOUT THE ENTIRE FOUNDING AREA. IT IS FURTHER SUGGESTED THAT THE AREA OF THE FOOTING CONTACT NOT BE SUBJECTED TO PROLONGED ATMOSPHERIC EXPOSURE, AND THAT THE EXCAVATIONS BE WELL DRAINED AT ALL TIMES.

UNCONFINED COMPRESSION TESTS ON SIMILAR SHALE BEDROCK INDICATE A CRUSHING STRENGTH ON THE ORDER OF 100 TONS PER SQUARE FOOT.







**LEGEND**

-  Auger Boring Location - Plan View.
-  Press and/or Drive Sample and/or Core Boring Location - Plan View.
-  Drive Rod Penetration Resistance Sounding Location - Plan View.
-  Capped Pile
-  Footing
-  Footing on Pile
-  TR Top of Rock
-  Prop. Footing 1993















 Horizontal Bar on Boring Log Indicates the Depth the Sample Was Taken.

 Figures Beside the Boring Log in Profile Indicate the Number of Blows for Standard Penetration Test.  
X = Number of Blows for First 6 inches.  
Y = Number of Blows for Second 6 inches.

**Drive Rod Penetration Resistance Sounding Log - Profile**

-  Casing
-  Resistance "R" < 10,000 lbs.
-  Resistance "R" > 10,000 lbs.
-  Z Indicates Final Measurement of Penetration, in Inches.
-  W Indicates Free Water Elevation.
-  V Indicates Static Water Elevation.

**SYMBOLS OF ROCK TYPES**

-  Coal
-  Weathered Mudstone or Claystone
-  Mudstone or Claystone
-  Weathered Shale
-  Shale
-  Weathered Siltstone
-  Siltstone
-  Weathered Sandstone
-  Sandstone
-  Leached Dolomite
-  Dolomite
-  Leached Limestone
-  Limestone
-  Boulders or Cobbles

**GENERAL INFORMATION**

**Drive Rod Penetration Sounding Test**

Drive rod penetration resistance tests constitute driving a 1.315-inch diameter steel rod, with a 45° cone point, into the ground using a 122-pound drop-hammer with a free fall of five feet. At one or two-foot depth intervals, a measurement is taken to determine the amount of penetration achieved in three hammer drops. This reading is converted to an empirical value for capacity "R", in thousands of pounds (which is a measure of both the point resistance and frictional resistance on the rod), using charts prepared by the Ohio Department of Highways, Bureau of Bridges, on the basis of correlation study of rod penetration with past performance of pile driving. For interpretation, a graph is prepared by plotting the value "R" against the depth at which the reading was taken, and connecting the plotted points. The curve so obtained reflects the density of subsurface materials in a manner that can be readily compared with data from similar tests at other locations on the structure site. From this comparison, the overall uniformity of subsurface conditions may be evaluated.


**Drive Sample Borings - Drive-Press Sample Borings**

Drive sample borings are made by means of a rotary-type drill rig, employing a 2" O.D., 1-3/8" I.D. sampler, at 2-1/2 foot or 5-foot depth intervals, driven by means of a 140-pound drop-hammer with a free fall of 30 inches. The number of blows required to drive the sampler 12 inches is considered the standard penetration test.

Drive-press sample borings are made by means of a rotary-type drill rig, employing a 2" O.D., 1-3/8" I.D. drive sampler, and a 2" O.D. thin-wall press sampler. The press sampler is advanced by continuous uniform pressure applied by the drill rig.

The boring log sheets show a graphic plot of the information obtained, including depth and elevation of the sample, number of blows for the standard penetration tests in two 6-inch increments, depth of press sample, field sample number, sample description - based on laboratory tests and the Casagrande classification system - and gradation, plasticity, and moisture content determinations. Results of strength and consolidation testing, if performed, appear on separate enclosures.

At depths where materials are bouldery or gravelly to the extent that the sampler can not be driven, a wash sample is procured for visual classification, in order to determine the general character of the material. Wash samples are not considered sufficiently representative to warrant laboratory testing.



NOTE: Information shown by this subsurface investigation was obtained solely for the use in establishing design controls for the project. The State of Ohio does not guarantee the accuracy of this data and it is not to be construed as a part of the plans governing construction of the project.

OHIO DEPARTMENT OF HIGHWAYS  
TESTING LABORATORY  
1600 WEST BROAD STREET, COLUMBUS, OHIO 43223

STRUCTURE FOUNDATION INVESTIGATION  
BRIDGE NO. CUY-480-1557 & 1559  
UNDER RAMP OBW-JN  
AND LANE JN-OBE  
CUY-480-15.22

CHECKED BY	REVIEWED BY	DATE
R. D. R.	G. P. H.	4/17/72

REV. JAN. 1993