

* - IN PLACE OF LANE LINE

| LOCATION AND STATION | | 828 | | | | | | | | | | 621 | | | | | |
|----------------------|---------|----------------|-----------------|---------------------|--------------------|------------|---------------------|--------------------------|-----------------------------------|------------------|---------------------------|---|----------|----------|--|----|-----|
| | | EDGE LINES | | LANE LINES | CHANNELIZING LINES | | STOP LINES | CROSSWALK LINES | TRANSVERSE LINES (WHITE) | LANE ARROWS | WORD ON PAVEMENT 96" | RAISED PAVEMENT MARKER, INSTALLATION ONLY | | | | | |
| | | WHITE LIN. FT. | YELLOW LIN. FT. | LANE LINES LIN. FT. | GORER LIN. FT. | * LIN. FT. | STOP LINES LIN. FT. | CROSSWALK LINES LIN. FT. | TRANSVERSE LINES (WHITE) LIN. FT. | LANE ARROWS EACH | WORD ON PAVEMENT 96" EACH | W EACH | W/R EACH | Y/R EACH | | | |
| S. R. 2 RAMPS | | | | | | | | | | | | | | | | | |
| RAMP J | 2+70.00 | 7+05.00 | 435 | 435 | | | | | | | | | | | | | 6 |
| RAMP M&N | 0+20.00 | 5+00.00 | 960 | 900 | | | 425 | 30 | 195 | | | 6 | 2 | | | 11 | 12 |
| RAMP M | 8+58.00 | 12+85.00 | 427 | 427 | | | | | | | | | | | | | 6 |
| RAMP N | 8+58.00 | 14+20.00 | 562 | 562 | | | | | | | | | | | | | 7 |
| RAMP O | 2+55.00 | 8+95.00 | 655 | 640 | | | | 25 | 70 | | | | | | | | 8 |
| RAMP S | 5+50.00 | 7+75.00 | 225 | 225 | | | | | | | | | | | | | 3 |
| | 7+75.00 | 11+75.00 | 430 | 415 | | | 780 | 40 | 95 | | | 9 | 2 | | | 20 | 6 |
| RAMP Q | 5+60.00 | 13+60.00 | 820 | 810 | | | | | | | | | | | | | 11 |
| RAMP V | | | | | | | | | | | | | | | | | |
| | 3+73.00 | 8+80.00 | 522 | 526 | | | 475 | 35 | 80 | | | 9 | 2 | | | 12 | 7 |
| | 8+80.00 | 10+95.00 | 215 | 215 | | | | | | | | | | | | | 3 |
| RAMP T | 1+71.00 | 9+70.00 | 810 | 800 | | | | | 35 | | | | | | | | 11 |
| RAMP B | 3+25.00 | 9+65.00 | 640 | 640 | | | | | | | | | | | | | 8 |
| | 9+65.00 | 11+15.00 | 170 | 160 | | | 130 | 30 | | | | 4 | 2 | | | 12 | 2 |
| RAMP A | 1+40.00 | 12+50.00 | 1120 | 1105 | | | | | | | | | | | | | 14 |
| RAMP C | 0+25.00 | 11+15.00 | 1095 | 1085 | | | | | | | | | | | | | 10 |
| RAMP D | 0+25.00 | 1+90.00 | 180 | 165 | | | 140 | 25 | | | | 4 | 2 | | | | 8 |
| | 1+90.00 | 6+55.00 | 465 | 465 | | | | | | | | | | | | | 2 |
| SHEET TOTAL | | | 9731 | 9575 | | | 1950 | 185 | 475 | | | 32 | 10 | | | 55 | 124 |
| | | | = 3.65 MILE | | | | 1950 | | | | | | | | | ** | 179 |

** QUANTITY CARRIED TO SHEET 62

PLOTTED FROM: I:\PROJECTS\19530\19530.DGN\19530tse.dgn

CALCULATED
G.J.N.
CHECKED
LDH

PAVEMENT MARKING / RAISED PAVEMENT MARKER
SUB-SUMMARY

LAKE COUNTY
LAK-2-6.12