CALC. BY: DATE:	LAKE/ASHTABULA COUNTY LAK/ATB-20-24.89/0.00 R/W ONLY		OHIO
CHK,D BY: DATE:			F.H.W.A. REGION 5
FEDERAL PROJECT		STATE PROJECT	

37

36
01-B-122-0-00-008-0
JOHN R. MEIVOGEL
11.61 Ac.

#3347
TRI-COUNTY
EQUIPMENT
REPAIR

39
01-B-122-0-00-006-0
BEVERLY J. &
JOSEPH WOITELLA
27.25 Ac.

COMM. 2-POLE SIGN
COMM. 2-POLE (NO SIGN)
GRASS
PC STA. = 444+20.06
TEMPORARY FENCE
CONSTRUCTION LIMITS
GRAVEL ± 7.50' COMM. DRIVE N03°36'01"W
COMM. SIGN
POST
GRAVEL W/ CONC. APRON RES. DRIVE N 11.24° W ± 30.6'
W.F.
16" W.
12"
C.B.
MATCH LINE STA. 441+00
MATCH LINE STA. 445+00
442
443
℄ SURVEY AND R/W N70°10'03"E
444
CURVE 3
CONC. APRON
15"
12" S.
EX. 4 1/2" CONC. WALK
CONC.
M.H.
21"
15" S.
R/W
SAVE TREE IF POSSIBLE
12"
36"
30"
24"
18"
S 01°21'03" W
S27°
CONSTRUCTION LIMITS
SEWER EASEMENT

34
01-B-122-0-00-017-0
DONALD MAH
29.10 Ac.

40
01-B-122-0-00-026-0
GORDON W. &
HELDA C. HOINES
0.45 Ac.

GRAVEL ± 72.52' RES. DRIVE S03°44'30"E
36.52'
2-STORY BRICK #5536

41
01-B-122-0-00-019-0
RIDGE MANOR NURSERIES INC.
18.0 Ac.

LAKE COUNTY
MADISON TOWNSHIP
TRACT 4
LOT 4

NOTE:
EXISTING RIGHT OF WAY LOCATION AND WIDTH DETERMINED FROM:
- PRIOR RIGHT OF WAY PLAN, DATED 1940.
- SURVEY BY: WESTERN RESERVE ENGINEERING & SURVEYING CO., 1992

CURVE 3 DATA
PI STA. 448+45.06
Δ = 01°58'50"
R = 24587.32'
D = 00°13'59"
T = 425.00'
L = 849.92'
C = 849.87'
S = NONE

N70°10'06"E 167.43'
S68°28'19"W 168.74'
36T
S00°57'03"W 10.70'
441+38.67 55.00' LT.
441+34.87 45.00' LT.
N00°57'03"E 48.13'
441+17.78 0.00' LT.
39T
N70°05'09"E 460.93'
S70°10'03"W 285.19'
S70°18'31"W 438.63'
444+20.06 45.00' LT.
723.73' OBS. No Deed Distance
300.00' D & U
100.00' D & U
443+32.68 0.00' RT.
444+20.06 0.00' RT.
444+32.68 0.00' RT.
S01°21'03"W 42.90'
N70°09'20"E 15.44'
S70°09'32"W 15.44'
444+32.61 40.00' RT.
S01°21'03"W 5.25'
444+43.32 40.00' RT.
34-A
40
41
41-A
N70°10'03"E 337.25'
S70°10'03"W 335.31'
S70°10'03"W 300.00'
443+17.19 40.00' RT.
S01°21'03"W 5.29'
N64°49'57"W 7.07'
S25°10'03"W 7.07'
S01°21'03"W 5.25'
100.00'
443+15.29 45.00' RT.
S01°21'03"W 10.80'
S01°21'03"W 10.79'
N70°25'09"E 381.90'
R=24632.32'
L=383.85'
C=383.85', S69°40'17"W
S69°19'54"W 684.00'
444+41.38 45.00' RT.
N01°21'03"E 10.73'
444+37.50 55.00' RT.
444+30.67 45.00' RT.
S01°21'03"W 10.84'
34T
40T
41T
41T-A
443+11.37 55.00' RT.
443+43.00 55.00' RT.
443+50.00 60.00' RT.
443+65.00 60.00' RT.
443+70.00 55.00' RT.
444+11.37 55.00' RT.
444+26.80 55.00' RT.
S70°10'03"W 33.63'
S70°10'03"W 15.00'
S70°09'55"W 41.37'

COMPLETION DATE:

REV.	DATE	DESCRIPTION

RIGHT-OF-WAY PLAN U.S. 20 STA. 441+00 TO STA. 445+00

NORTH EASTERN ROUTE

Filename = K:\RDL\10001\19175\STRUCT\19175887
Plot Scale = 1 / 40
Drawn By/Date = DN / 02-23-94 (14)