



EROSION CONTROL		
659		
COMMERCIAL FERTILIZER	SEEDING AND MULCHING	AGRICULTURAL LIMING
TONS	SQ. YDS.	TONS
.07	734	.33

PAVEMENT								
STATION	SIDE	301	310	403	404	408	609	
		BITUMINOUS AGGREGATE BASE	SUBBASE GRADING "B"	ASPHALT CONCRETE	ASPHALT CONCRETE	PRIME COAT	STANDARD TYPE "B" CURB	
FROM	TO	CUBIC YARDS				GALS.	LIN. FT.	
567+00	568+80	R	21	12	7	4	44	180
567+00	568+80	L	22	12	7	4	44	180
568+80	570+51	R	14	8	5	2	28	171
568+80	570+51	L	13	8	5	2	28	165
TOTALS			70	40	24	12	144	696

ROADWAY								
STATION	SIDE	201	202		203		EMBANKMENT	
		STUMP REMOVED 60"	SIDEWALK REMOVED	CURB REMOVED	WEARING COURSE REMOVED	EXCAVATION NOT INCLUDING EMBANKMENT		
FROM	TO	EACH	SQ. FT.	LIN. FT.	SQ. YD.	CU. YD.	CU. YD.	
567+00	570+45	L	1	1725	345	39		
567+00	570+51	R		1592	351	39		
TOTALS			1	3317	696	78	273	31

CURB TRANSITION
Transition curb from a height of 2' to the proposed height of 6" in ten linear feet

DRAINAGE				
STATION	SIDE	603	604	202
		12" CONDUIT TYPE "B"	STANDARD N° 3-A CATCH BASIN	CATCH BASIN ABANDONED
FROM	TO	LIN. FT.	EACH	EACH
569+00	L	5	1	1
569+00	R	5	1	1
TOTALS		10	2	2