

CALC. BY J.C.
DATE 12/10/88
CHKD. BY J.M.
DATE 4/24/88

LAKE COUNTY
LAK - 306 - 6.50

OHIO
FHWA REGION 5

8
38

DRIVE SUB-SUMMARY

SHEET NO.	☉ DRIVE STATION	SIDE	ITEM 452 - 8" PLAIN CONCRETE PAVEMENT (SQ. YDS.)	ITEM 404 - 1" ASPHALT CONCRETE, AC-20 (CU. YDS.)	ITEM 301 - 5" BITUMINOUS AGGREGATE BASE, AC-20 (CU. YDS.)	ITEM 202 - PAV'T REMOVED (SQ. YDS.)	ITEM 202 - CURB REMOVED (LIN. FT.)	
11	26+20	RT.	29.7	1.2	6.0			
11	26+85	RT.	18.9	0.6	3.1			
11	30+50	RT.	13.3	1.2	6.2	60		
12	31+27	RT.	13.9	0.9	4.6	52		
12	31+97	RT.	8.3	0.5	2.3			
12	32+23	LT.	11.1					
12	32+48	RT.	7.8	0.4	2.1			
12	34+09	RT.				75	22	
12	35+66	RT.	16.1	0.7	3.7	45	12	
12	36+81	RT.	16.7	0.8	3.9	45	12	
13	38+06	RT.	17.8	0.8	4.2		52	
13	40+03	RT.	78.0			125	62	
13	40+08	LT.	27.8			49		
13	41+78	RT.				132	88	
14	43+87	RT.	97.5			125	60	
TOTALS (CARRIED TO GENERAL SUMMARY)			357	7	36	708	308	

STATE ROUTE 306