



FED. NO.	STATE	PROJECT	
2	OHIO	LAK-44-3.79	166 204

LAK-44-3.79

16 gauge x 0-6" copper flashing, Type A

1/4" Preformed asphalt protection blocks

3 Ply membrane waterproofing, Type C

3 ply membrane waterproofing, Type C

1/4" preformed asphalt protection blocks

3/4" Fabreeka Pad or an approved equal.

12 x 1/4" R and 2-1/2 x 1/2" anchors @ 18" c/c.

Face of backwall

1/4" V groove

1/4" Preformed expansion joint filler

Surface of concrete deck

Seal with hot poured joint sealer, Sec. M-10.23

1/2" Min. expansion joint filler

1/4" Preformed expansion joint filler

3/4" Fabreeka Pad, or equal

1/2" R anchors

1/2" R anchors

DESIGNED	DRAWN	TRACED	CHECKED	REVIEWED	DATE	REVISED
MPB	MPB		WCK	BFG	8-8-61	

LAKE COUNTY Sta. 271+64.18

STATE OF OHIO
 DEPARTMENT OF HIGHWAYS
 DIVISION OF DESIGN AND CONSTRUCTION
 BUREAU OF BRIDGES

SUPERSTRUCTURE DETAILS
 BRIDGE NO LAK-44-0483
 under
 N.Y.C. & ST. L. R.R.