

Lake

COUNTY, SECTION

LAK-44-7.22

| REF. NO. | ITEM NO. | APPROXIMATE QUANTITIES | ITEM | UNIT PRICE | | TOTAL | | |
|-------------|----------------|------------------------|--|------------|-------|---------|-------|--|
| | | | | DOLLARS | CENTS | DOLLARS | CENTS | |
| PAVEMENT | | | | | | | | |
| 97 | B-19 | 4,612 | cu. yds. aggregate base course | | | | | |
| 98 | B-21 | 2,079 | cu. yds. waterproofed aggregate base course | | | | | |
| 99 | B-35 | 184 | cu. yds. asphaltic concrete leveling course (70-85) | | | | | |
| 100 | B-35 | 293 | cu. yds. asphaltic concrete base course (70-85) | | | | | |
| 101 | I-7 | 340 | sq. yds. reinforced concrete approach slabs (T=13") | | | | | |
| 102 | I-12 | 1,160 | lin. ft. Standard Type 6 concrete curb | | | | | |
| 103 | I-12 | 24,096 | lin. ft. Standard Type 2-A concrete curb | | | | | |
| 104 | I-12 | 400 | lin. ft. special Portland cement concrete curb, as per plan | | | | | |
| 105 | I-18 | 3,839 | cu. yds. stabilized crushed aggregate shoulders and approaches | | | | | |
| 106 | I-21 | 461 | sq. yds. 4" Portland cement concrete median pavement, Standard Type 1 | | | | | |
| 107 | I-22 | 24,010 | cu. yds. subbase, Grading "A" or "B", as per plan | | | | | |
| 108 | I-23 | 56 | each standard precast white Portland cement concrete traffic dividers | | | | | |
| 109 | T-30 | 9,731 | gals. bituminous prime coat: Sec. M-5.7, RT-2 or RT-3 | | | | | |
| 110 | T-31 | 6,239 | gals. bituminous surface treatment, bituminous material, as per plan | | | | | |
| 111 | T-31 | 201 | cu. yds. bituminous surface treatment, No. 6 aggregate | | | | | |
| 112 | T-32 | 22,390 | gals. road mix bituminous material: Sec. M-5.2, RC-2 or RC-3; or Sec. M-5.3, MC-4 or MC-5; or Sec. M-5.7, RT-8 or RT-9 | | | | | |
| 113 | T-32 | 5,088 | gals. seal coat bituminous material: Sec. M-5.2, RC-3 or RC-4; or Sec. M-5.3, MC-4 or MC-5; or Sec. M-5.7, RT-9 or RT-10 | | | | | |
| 114 | T-32 | 1,142 | cu. yds. No. 46 aggregate for road mix | | | | | |
| 115 | T-32 | 84 | cu. yds. No. 6 aggregate for choke | | | | | |
| 116 | T-32 | 165 | cu. yds. No. 6 aggregate for seal coat | | | | | |
| 117 | T-35 | 181 | cu. yds. asphaltic concrete surface course, Type "C" (70-85) | | | | | |
| 118 | T-71 | 88,220 | sq. yds. 9" reinforced Portland cement concrete pavement | | | | | |
| 119 | Special | 1,651 | sq. yds. mixing calcium chloride and crushed aggregate | | | | | |
| 120 | TOTAL PAVEMENT | | | | | | | |
| WATER LINES | | | | | | | | |
| 121 | I-124 | 350 | lin. ft. 6" new water main, cement mortar lined pipe | | | | | |
| 122 | I-124 | 1,720 | lin. ft. 10" new water main, cement mortar lined pipe | | | | | |
| 123 | I-124 | 417 | lin. ft. 16" new water main, cement mortar lined pipe | | | | | |
| 124 | I-124 | 80 | lin. ft. 24" new water main with dresser style 60 bell joint clamps, or an approved equal | | | | | |
| 125 | I-124 | 2 | each 10" cast iron fittings (1/32 bend) | | | | | |
| 126 | I-124 | 1 | each 10" cast iron fitting (1/8 bend) | | | | | |
| 127 | I-124 | 1 | each 10" cast iron fitting (10" tee) | | | | | |
| 128 | I-124 | 3 | each 10" cast iron fittings (plugs or caps) | | | | | |
| 129 | I-124 | 1 | each 10" cast iron fitting (10"x8" reducer) | | | | | |