STATE OF OHIO DEPARTMENT OF HIGHWAYS

SUPPLEMENTAL SPECIFICATION NO. 18 FENCE AND GATES

Revised June 15, 1959

Description

ing and grades shown on the Plans, including the necessary excavating and concreting; creosoting and/or painting or galvanizing the components of the fence; to result in a completed fence of the type and dimensions required by these Specifications, and the Plans, Special Provisions and Proposal. The Item shall consist of the following; furnishing all necessary posts, fastenings, anchors, braces, fabric, barbed wire, stretcher bars, top rails, and gates and fittings; preparing, assembling, setting, stretching, and erecting the fence in the location and to the furnishing all necessary

Link Fence, as specified. Type C Chain Link l galvanized steel or aluminum unless otherwise Fence shall be either Type A Woven Steel Wire Fence or Type C Chain Fence, as specified. Type C Chain Link Fence shall be either specified.

Wire-Gage

All wire gage numbers specified refer tion and (formerly Material Washburn and Moen) Specifications. specified to the Steel Wire Gage Construc-

MATERIALS

Type A Woven Steel Wire Fence

Fabric. Woven steel wird Designation A 116, Class steel wire w fabric shall meet the requirements of ASTM

fabric shall also meet the following requirements:

1047-6-9 939-6-9	Design Number
9 01	No. of Bars
47 39	Nominal Height inches
00	Spacing of Stays inches
99	Top
99	Gage of Wire
9	re Filler