



**Note:**  
 The existing 8" Water Main is to be relocated in the vicinity of Structure No. LA-535-0A by the Village of Fairport and the work will not be a part of this contract. The contractor shall cooperate to the fullest extent with the Village of Fairport while this work is being performed.

SEWERS							
Item No	Station	Side	Structure	Adjust. M.H. To Grade	Abandon C.B.	12" Pipe for Storm Sewer	Abandon C. Inlet
		L or R	Each	Each	Each	Each	Each
1-5	33+20	R	1	1			
2-5	33+70-33+80	L & R	2	1	1	14	
3-5	34+95	R	1				
4-5	37+00	L	1			28	
5-5	37+05	R	1			28	
6-5	42+13	R	1				1
7-5	42+95	R	1				
8-5	43+20	R	1				
Total			4	4	1	70	1

\* Note: - One Manhole of the four to be adjust grade is a sanitary manhole in the City of Painesville

**MONUMENT BOX**  
 1-M Adjust Monument Box to Grade 1 Each

**REMOVAL & DISPOSAL OF EXISTING PAVEMENT - 2363 SQ. YDS.**  
**REMOVAL & DISPOSAL OF EXISTING S.S. CURB. - 398 LIN. FT.**  
**REMOVAL & DISPOSAL OF EXISTING GUARD RAIL - 845 LIN. FT.**

Excavation 7398 Cu. Yds.  
 Embankment 51 Cu. Yds.  
 Emb. +22% 62 Cu. Yds.

Seeding & Protecting 6,222 Sq. Yds.  
 Commercial Fertilizer (10-6-4)  
 6,222 Sq. Yds. x 9 = 55,998 = 1000 = 55.99 x 20 =  
 = 1119.80 lbs. ÷ 2000 = 55.99 Tons Use .56 Tons

Excavation 1784 Cu. Yds.  
 Embankment 4911 Cu. Yds.  
 Emb. +22% 5991 Cu. Yds.

Seeding and Protecting 5626 Sq. Yds.  
 Commercial Fertilizer (10-6-4)  
 5626 Sq. Yds. x 9 = 50,634 ÷ 1000 = 50.63 x 20 = 1,012.60 lbs.  
 ÷ 2000 = .5063 Tons Use .51 Tons.