



Existing Steps to be Removed by Highway Contractor

New Steps & Entrance by Others

PAVEMENT			
REF.	LOCATION	S.F.	L.F.
30	8+71.60 to 8+75 (M)	400	
31	8+75 (M) to 10+56	1679	
32	11+73	62	45
33	12+26	49	28
34	12+62 to 13+25	436	
35	8+80 to 9+04	120	
36	9+40 to 10+57 (M)	300	
37	10+81 (M) to 11+00 (M)	95	
38	11+09 (M) to 10+99	325	
39	11+36 to 11+60	120	
40	11+95 to 13+25	650	
41	10+41 to 11+70	614	
42	11+22 (M) to 11+25 (M)	15	
43	11+05		43
44	11+70 to 12+62	470	
TOTAL		4959	116

(M) = Mentor Avenue Stationing

PAVEMENT				203	451	452	609
REF.	LOCATION	S.Y.	Subgrade Compaction	Reinforced Concrete	Plain Concrete	Curb	Std. Type 2A
REF.	LOCATION	S.Y.		S.Y.	S.Y.	L.F.	
1	8+71.60 to 8+75 (M)					100	
2	8+75 (M) to 9+66.48 (M)	802		802			
3	8+75 (M) to 9+35 (M)					60	
4	9+42 (M) to 12+20					230	
5	12+27 to 13+25					98	
6	8+71.60					9	
7	8+71.60 to 8+95					24	
8	9+27					37	
9	9+02 to 11+25 (M)					170	
10	10+64 (M)					26	
11	11+16 (M)					20	
12	10+34 (M) to 11+25 (M)	828		828			
13	11+16 (M)					9	
14	11+25 (M) to 12+20					206	
15	11+13					33	
16	11+82					39	
17	8+71.60 to 13+25	3174		3174			
18	12+27 to 13+25					98	
TOTAL		4804		4804	179	986	