



CURVE DATA
 $D = 92^{\circ}24'45''$
 $\Delta = 52^{\circ}06'30''$
 $T = 30.31'$
 $E = 701'$
 $L = 56.39'$
 $R = 62.00'$
 $PI = 51+30.99$

In lieu of the pavement shown on sheet 53, the portion of this drive behind the concrete apron shall be paved with 10" of Item 304.
 For driveway profile see Sheet 33.

QUANTITY CALCULATIONS
 BY: *RR* DATE: 5-23-68
 CHKD: *GBB* DATE: 5-28-68
 BURGESS & NIPLER, LIMITED

REF.	LOCATION	PAVEMENT										
		Subgrade	Compaction	Aggregate Base	Subbase	Grading A	Asphalt Concrete (70-85)	Asphalt Concrete (70-85)	Bituminous Prime Coat	Plain Concrete	Concrete Walk	Curb
S.Y.	C.Y.	C.Y.	C.Y.	C.Y.	C.Y.	C.Y.	GAL.	S.Y.	S.F.	L.F.		
1	50+02			60								
2	49+69 to 52+00										243	
3	51+85.50			276					25			
4	49+78			5					10			
5	49+69 to 52+00	642			60				642			
6	49+69 to 52+00											219
7	52+00 to 52+50	122	10	29		4	4	53				
8	51+08 to 51+23											60
TOTAL		764	10370	60	4	4	53715	60462				