



** - BARS SHALL BE EQUALLY SPACED BETWEEN PILES AT 18" MAXIMUM.

- NOTES:
1. FOR REAR ABUTMENT PLAN AND ELEVATION, SEE SHEET 16/41.
 2. SEE "DOWEL HOLES" GENERAL NOTE ON SHEET 4/41 FOR INSTALLATION AND PAYMENT INFORMATION.
 3. THE SECOND SEALING COAT ONLY SHALL BE TINTED TO FEDERAL COLOR STANDARD 59B-25630 SEMI-GLOSS.
 4. NOTATION: EL.-ELEVATION; E.F.-EACH FACE; TYP.-TYPICAL CIPRCP-CAST-IN-PLACE REINFORCED CONCRETE PILES; CLR.-CLEAR; SPA.-SPACES; DWL.-DOWEL.

CT Consultants
Engineers • Architects • Planners

DATE: 10/26/01
REVIEWED: J.E.A.
DRAWN: R.L.B.
DESIGNED: I.A.S.
CHECKED: J.P.R.

STRUCTURE FILE NUMBER: 4304055

REAR WINGWALL DETAILS
BRIDGE NO. LAK-90-0945
S.R. 615 OVER INTERSTATE 90

LAK-IR90/SR615-
9.26/1.51

17 / 41

344
393