



**LEGEND**

\* TAPER CURB FROM 150 mm TO 0 mm IN 3.0 METERS.

REMOVE 0.6 m MINIMUM OF EXISTING ASPHALT

194					191.505		191.841		191.000	192.236	194
193											193
192											192
191	0.475%		0.025%					1.957%		2.000%	191
190											190
189											189
188											188
187											187
186											186
185											185
191.275	0+900	191.180	0+920	191.185	0+940	191.505	0+960	191.785	0+980	192.030	1+000

FOR TYPICAL SECTIONS, SEE SHEETS 3-7  
 FOR ROADWAY, DRAINAGE AND SANITARY QUANTITIES, SEE SHEET 92  
 FOR CROSS SECTIONS AND PIPE PROFILES, SEE SHEETS 111-122  
 FOR INTERSECTION DETAILS, SEE SHEETS 123-129  
 FOR DRIVEWAY PROFILES, SEE SHEETS 130-137  
 FOR DRIVEWAY DETAILS, SEE SHEET 138  
 FOR DRAINAGE DETAILS, SEE SHEETS 139-140  
 FOR WATER WORK DETAILS, SEE SHEETS 141-144  
 FOR MONUMENT LOCATIONS, SEE SHEET 2  
 FOR SIGNAL PLAN, SEE SHEETS 150-158  
 FOR SIGNING PLAN, SEE SHEETS 165-168  
 FOR PAVEMENT MARKING DETAILS, SEE SHEET 159-164  
 FOR SAW CUT AT EXISTING PARKING LOTS, SEE SHEET 138  
 FOR SUB-SUMMARIES, SEE SHEETS 32-43

H: /1998/98208/SDSK/E355.DWG