



NOTE:  
ALL STATIONING  
IS ON TANGENT

NOTE: ITEM S-6, PNEUMATICALLY PLACED MORTAR, SHALL INCLUDE FILLING ALL DETERIORATED AREAS, AS DIRECTED BY THE ENGINEER, TO FORM A TRUE PLANE WITH EXISTING FACE OF WALL. AREAS WITH DEPRESSIONS OVER 1/2\"/>

EXIST TIE RODS ARE LOCATED APPROXIMATELY 15\"/>

I-15 GUARD RAIL REMOVAL						
REF.	STATION		GUARD RAIL TO BE REMOVED & DISPOSED OF		GUARD RAIL TO BE REMOVED & REBUILT	
	FROM	TO	SIDE	LIN. FT.	SIDE	LIN. FT.
I-G	12+68.7	16+00			LT.	326
I-R	13+24	14+27	LT.	103		
TOTAL NORMAL PARTICIPATION				103		326

I-13 4\"/>				
REF.	STATION	SIDE	SQ. FT.	
I-13	12+68.7	13+53	LT.	328
I-13	12+66	13+50	RT.	445
TOTAL NORMAL PARTICIPATION				773

E-8 SIDEWALK REMOVAL				
REF.	STATION	SIDE	SQ. FT.	
	FROM	TO		
E-8	12+68.7	16+00	LT.	2344
E-8	12+66	13+53	RT.	460
TOTAL NORMAL PARTICIPATION				2804

SPECIAL WROUGHT IRON FENCE REMOVAL				
REF.	STATION	SIDE	LIN. FT.	
	FROM	TO		
I-F	12+68.7	16+00	LT.	327
TOTAL NORMAL PARTICIPATION				327

SS-18 FENCE TYPE C				
REF.	STATION	SIDE	LIN. FT.	
	FROM	TO		
I-FS	12+68.7	16+00	LT.	327
TOTAL NORMAL PARTICIPATION				327

S-6 PNEUMATICALLY PLACED - MORTAR				
REF.	STATION	SIDE	SQ. FT.	
	FROM	TO		
I-P	11+11.5	12+68.7	LT.	1880
TOTAL				1880

S-22 REMOVAL OF PORTIONS OF EXISTING STRUCTURE		
STATION	UNIT	
FROM	TO	
13+79	15+57	LUMP SUM

* L-9 SEEDING & PROTECTING QUANTITIES						
STATION		SEEDING & PROTECTING		COMMERCIAL FERTILIZER		AGRICULTURAL LIMING MATERIAL
FROM	TO	AREA SQ. FT.	AREA SQ. YDS.	AREA SQ. FT.	AREA X 0.01 TON/1000'	AREA X 0.05 TON/1000'
12+66	13+47	493	55	493	0.01	493
13+86.7	16+00	1301	145	1301	0.01	1301
TOTAL NORMAL PARTICIPATION			200		0.02	0.09

* I-8 CASTINGS ADJUSTED TO GRADE						
REF.	STATION	MON. BOX	INLET BASINS	STORM M.H.'S	SANITARY M.H.'S	I-124 Water Valve Box Adj. to Gr.
	FROM	TO	EACH	EACH	EACH	EACH
I-M	12+68.7	16+00	1			
I-B	12+68.7	16+00		3		
I-ST	12+68.7	16+00			1	
I-SA	12+68.7	16+00				1
I-W	12+68.7	16+00				3
100% PAINESVILLE PART.						3
TOTAL NORMAL PARTICIPATION			1	3	1	3

T-70 7\"/>			
REF.	STATION	SIDE	SQ. YDS.
I-A	14+73	R	8
2-A	15+23	R	8
3-A	15+88	R	7
TOTAL			23

ROADWAY QUANTITIES						
STATION		T-71 REINFORCED PORTLAND CEMENT PAVEMENT	I-12 CONCRETE CURB TYPE - 2A	E-8 REMOVAL & DISPOSAL OF EXISTING CURB	E-8 REMOVAL & DISPOSAL OF EXISTING PAVEMENT	E-1 COMPACTED SUBGRADE
FROM	TO	SQ. YDS.	LIN. FT.	LIN. FT.	SQ. YDS.	SQ. YDS.
14+04	16+00	674	392	392	653	674
12+68.7	14+04	SEE EXTRA AREA SHEET 7				
TOTAL NORMAL PARTICIPATION		674	392	392	653	674

\* FOR ADDITIONAL L-9 QUANTITIES SEE SHEETS 8, 9 & 10

\* SEE GENERAL NOTES