

RESURFACING QUANTITIES

PART 1

RESURFACING QUANTITIES					
LOCATION		SIDE	END WIDTHS	254	446
				PAVEMENT PLANING, BITUMINOUS	1 1/4" ASPHALT CONCRETE SURFACE COURSE, TYPE I, AC-20, AS PER PLAN
FROM	TO		LIN FT	SQ YDS	CU YDS
IR 271					
52+00	53+50	NB	56	933.3	32.4
52+00	58+97.97	SB	64.5	5002.1	173.7
53+50	59+00.35	NB	75	4586.3	159.2
58+97.97	62+67.71	SB	34	1396.8	48.5
59+00.35	60+00	NB	46	509.3	17.7
60+00	62+50	NB	44	1222.2	42.4
62+50	64+10	NB	42	746.7	25.9
64+10	90+53	NB	38	11159	387.5
62+67.71	63+88	SB	43	574.7	19.9
63+88	64+00	SB	44	58.7	2.0
64+00	65+60	SB	42	746.7	25.9
65+60	90+63.78	SB	38	10572	367.1
90+53	92+40.11	NB	43	894	31
90+63.78	92+40.11	SB	70.5	1381.3	48.0
IR 90					
92+40.11	98+16.34	WB	59.5	3809.5	132.3
92+40.11	98+58.04	EB	63.5	4359.8	151.4
98+16.34	102+63.97	WB	46.5	2312.8	80.3
98+58.04	104+34.04	EB	48	3072	106.7
102+63.97	114+00	WB	57.5	7258	252.0
104+34.04	110+30	EB	46.5	3079.1	106.9
110+30	111+30	EB	52.5	583.3	20.3
111+30	114+00	EB	58.5	1755	60.9
114+00	114+63.97	WB	69.5	494.0	17.2
114+00	116+72.53	EB	58.5	1771.4	61.5
114+63.97	117+56	WB	49.5	1606.2	55.8
116+72.53	123+34	EB	72	5291.8	183.7
117+56	132+50	WB	46.5	7719	268.0
123+34	124+34	EB	48.5	538.9	18.7
124+34	133+77	EB	41.5	4348.3	151.0
132+50	135+00	WB	40.5	1125.0	39.1
133+77	136+34	EB	39.5	1127.9	39.2
135+00	141+17	WB	34.5	2365.2	82.1
136+34	138+49.60	EB	34.5	826.5	28.7
138+49.60	149+45.45	EB	51	6209.8	215.6
141+17	142+17	WB	35.5	394.4	13.7
TOTAL - PART 1				64850	2252

PART 2

RESURFACING QUANTITIES					
LOCATION		SIDE	END WIDTHS	254	446
				PAVEMENT PLANING, BITUMINOUS	1 1/4" ASPHALT CONCRETE SURFACE COURSE, TYPE I, AC-20, AS PER PLAN
FROM	TO		LIN FT	SQ YDS	CU YDS
IR 271					
52+00	53+50	NB	56	933.3	32.4
52+00	58+97.97	SB	64.5	5002.1	173.7
53+50	59+00.35	NB	75	4586.3	159.2
58+97.97	62+67.71	SB	34	1396.8	48.5
59+00.35	60+00	NB	46	509.3	17.7
60+00	62+50	NB	44	1222.2	42.4
62+50	64+10	NB	42	746.7	25.9
64+10	90+53	NB	38	11159	387.5
62+67.71	63+88	SB	43	574.7	19.9
63+88	64+00	SB	44	58.7	2.0
64+00	65+60	SB	42	746.7	25.9
65+60	90+63.78	SB	38	10572	367.1
90+53	92+40.11	NB	43	894	31
90+63.78	92+40.11	SB	70.5	1381.3	48.0
IR 90					
92+40.11	98+16.34	WB	59.5	3809.5	132.3
92+40.11	98+58.04	EB	63.5	4359.8	151.4
98+16.34	102+63.97	WB	46.5	2312.8	80.3
98+58.04	104+34.04	EB	48	3072	106.7
102+63.97	114+00	WB	57.5	7258	252.0
104+34.04	110+30	EB	46.5	3079.1	106.9
110+30	111+30	EB	52.5	583.3	20.3
111+30	114+00	EB	58.5	1755	60.9
114+00	114+63.97	WB	69.5	494.0	17.2
114+00	116+72.53	EB	58.5	1771.4	61.5
114+63.97	117+56	WB	49.5	1606.2	55.8
116+72.53	123+34	EB	72	5291.8	183.7
117+56	132+50	WB	46.5	7719	268.0
123+34	124+34	EB	48.5	538.9	18.7
124+34	133+77	EB	41.5	4348.3	151.0
132+50	135+00	WB	40.5	1125.0	39.1
133+77	136+34	EB	39.5	1127.9	39.2
135+00	141+17	WB	34.5	2365.2	82.1
136+34	138+49.60	EB	34.5	826.5	28.7
138+49.60	149+45.45	EB	51	6209.8	215.6
141+17	142+17	WB	35.5	394.4	13.7
SUB-TOTAL COLUMN 2				99831	3466.3

PART 2

RESURFACING QUANTITIES					
LOCATION		SIDE	END WIDTHS	254	446
				PAVEMENT PLANING, BITUMINOUS	1 1/4" ASPHALT CONCRETE SURFACE COURSE, TYPE I, AC-20, AS PER PLAN
FROM	TO		LIN FT	SQ YDS	CU YDS
142+17	146+69.73	WB	60	3018.2	104.8
146+69.73	147+69.73	WB	40.5	450	15.6
147+69.73	214+83.73	WB	34.5	25737	893.6
149+45.45	159+00	EB	34.5	3659.1	127.1
159+00	160+00	EB	40.5	450	15.6
160+00	164+54.73	EB	60	3031.5	105.3
164+54.73	165+55	EB	36.5	406.7	14.1
165+55	178+85	EB	34.5	5098.3	177.0
178+85	183+50	EB	41	2118.3	73.6
183+50	194+50	EB	47	5744.4	199.5
194+50	214+83.73	EB	34.5	7796.0	270.7
222+01.66	232+41.54	EB	34.5	3986.2	138.4
234+57.10	250+00	EB	34.5	5914.5	205.4
222+01.66	235+38.42	WB	34.5	5124.3	177.9
237+26.78	250+00	WB	34.5	4880.7	169.5
250+00	269+83.49	EB	34.5	7603.4	264.0
271+32.07	273+53.50	EB	34.5	848.8	29.5
276+46.5	285+00	EB	34.5	3271.8	113.6
250+00	271+21.44	WB	34.5	8132.2	282.4
272+56.44	273+53.50	WB	34.5	372.1	12.9
276+46.50	293+65.57	WB	34.5	6589.8	228.8
296+30.43	333+45.58	WB	34.5	14241	494.5
285+00	293+65.57	EB	34.5	3318.0	115.2
296+30.43	334+19.09	EB	34.5	14523	504.3
333+45.58	345+45.58	WB	47	6266.7	217.6
334+19.09	335+19.09	EB	40.5	450	15.6
SUB-TOTAL COLUMN 3				143032	4966.5

PART 2

RESURFACING QUANTITIES					
LOCATION		SIDE	END WIDTHS	254	446
				PAVEMENT PLANING, BITUMINOUS	1 1/4" ASPHALT CONCRETE SURFACE COURSE, TYPE I, AC-20, AS PER PLAN
FROM	TO		LIN FT	SQ YDS	CU YDS
335+19.09	341+86.59	EB	46.5	3448.8	119.8
341+86.59	346+19.09	EB	58	2787.2	96.8
345+45.58	349+00	WB	40	1575.2	54.7
346+19.09	347+17	EB	36.5	397.1	13.8
347+17	368+29	EB	34.5	8096.0	281.1
349+00	365+20	WB	34.5	6210.0	215.6
365+20	366+17.66	WB	41	444.9	15.4
366+17.66	370+08.5	WB	64.5	2801	97.3
368+29	373+15.16	EB	39.5	2133.7	74.1
370+08.5	375+00	WB	51	2785.2	96.7
373+15.16	375+00	EB	57.5	1180.9	41.0
10+99.63	13+17.29	WB	51	1233.4	42.8
10+99.63	21+14.83	EB	45	5076.0	176.3
13+17.29	14+17.29	WB	45	500	17.4
14+17.29	101+67.55	WB	39	37917.8	1316.6
21+14.83	35+00	EB	34.5	5309.8	184.4
35+00	101+67.55	EB	39	28893	1003.2
101+74.57	140+53.07	EB	39	16806.8	583.6
101+74.57	140+53.07	WB	39	16806.8	583.6
143+40.31	216+10.14	EB	39	31502.6	1093.8
143+40.31	230+00	WB	39	37525.3	1303.0
216+10.14	217+10.14	EB	45	500	17.4
217+10.14	221+03.31	EB	66.5	2905.1	100.9
221+03.31	222+03.31	EB	42	466.7	16.2
222+03.31	239+61	EB	39	7616.7	264.5
230+00	241+39.02	WB	51.5	6517.7	226.3
239+61	241+39.02	EB	47.1	931.6	32.3
242+80.20	245+80.20	EB	42.1	1403.3	48.7
242+80.20	247+66.20	WB	44	2376	82.5
245+80.20	258+84.37	EB	51.5	7462.8	259.1
247+66.20	263+36.12	WB	39	6803	236.2
258+84.37	280+89	EB	39	9553.4	331.7
263+36.12	264+36.12	WB	41	455.6	15.8
264+36.12	268+90.85	WB	64.5	3258.9	113.2
268+90.85	269+90.85	WB	45	500	17.4
269+90.85	280+89	WB	39	4758.7	165.2
I-90 (EUCLID SPUR)					
10+00	20+84.86	EB	46.5	5605.1	194.6
20+84.86	26+00	EB	53.5	3062.2	106.3
26+00	35+79.29	EB	38	4134.8	143.6
10+00	14+38.54	WB	46.5	2265.8	78.7
14+38.54	28+13.64	WB	59.5	9090.9	315.7
SUB-TOTAL COLUMN 4				293100	10177.3
TOTAL - PART 2				535963	18610

PLOT SUBMITTED BY: GRMOVSEK PLOT SUBMITTED: 4-MAY-1990 10:03 ZFI:[100,350]OLK90GBA.DGN;2