



NOTE: THE HANDICAPPED TELEPHONE BOOTH SHALL BE INSTALLED TO COMPLY TO ANSI A117.1, SECTION 4.31 THE PHONE SHALL BE PLACED SO THAT THE TOP MOST DIGIT OF THE DIAL AND HAND SET SHALL BE 48" FROM FINISHED FLOOR. MAKE NECESSARY ADJUSTMENTS AS REQUIRED TO BE IN COMPLIANCE.

WATER CLOSETS (INCLUDING HANDICAPPED)	1'-3"
LAVATORIES (INCLUDING HANDICAPPED)	2'-10"
URINAL (LOW MOUNTED)	1'-4"
URINAL (HIGH MOUNTED)	1'-10"

NOTE: THE TOP OF ALL MIRRORS SHALL BE MOUNTED 5'-10" OFF OF FINISHED FLOOR.

OHIO BUREAU OF DESIGN SERVICES		DEPARTMENT OF TRANSPORTATION	
MOTORIST SERVICES BUILDING & STORAGE UNIT			
REVISIONS	DATE	SHEET NO. RRA	
3-1-78		6C	
BY O.D.O.T.		DATE 9-1-78	
7-6-78			
9-26-78			
1-22-80			
2-11-81			
2-24-81			
10-13-82			

MASTER 1980