

GENERAL NOTES

B. CONDITIONS

DURING ALL PARTS OF THIS PROJECT, SIGNING, BARRICADES, FLASHING ARROWS, ETC. SHALL BE LOCATED AS INDICATED IN THE MANUAL OR AS SHOWN IN THE STANDARD DRAWINGS.

C. ADVANCE WARNING SIGNS

ALL ADVANCE WARNING SIGNS FOR ANY CONDITION WHICH RESTRICTS TRAFFIC SHALL BE ERECTED BEFORE ANY SUCH RESTRICTION IS PUT INTO EFFECT. ALL SUCH SIGNS SHALL BE COVERED OR REMOVED FROM THE VIEW OF TRAFFIC WHENEVER THEY ARE NOT APPLICABLE.

D. FLASHING ARROW REQUIREMENT

WHENEVER ANY PART OF THE TRAVELED SURFACE IS CLOSED, THE MOTORISTS SHALL BE WARNED AND DIRECTED BY THE CONTRACTOR THROUGH THE USE OF FLASHING ARROWS AS SHOWN IN THE STANDARD DRAWINGS.

E. FAILURE TO COMPLY

IF THERE IS ANY FAILURE TO COMPLY WITH PROVISIONS FOR TRAFFIC CONTROL SET OUT IN THESE PLANS AND NOTES, OR WITH THE PROVISIONS OF THE "MANUAL", THE HIGHWAY IN THE VICINITY OF THE WORK AREA SHALL NOT BE CONSIDERED IN A CONDITION FOR THE SAFE AND CONVENIENT USE BY THE TRAVELING PUBLIC. ANY FAILURE TO KEEP THE HIGHWAY, IN THE VICINITY OF THE WORK AREA, IN A CONDITION FOR THE SAFE AND CONVENIENT USE BY THE TRAVELING PUBLIC SHALL BE CONSIDERED A BREACH OF THIS CONTRACT. WORK SHALL BE SUSPENDED UNTIL THE CONTRACTOR COMPLIES WITH THE PROVISIONS OF THE AFOREMENTIONED ITEMS.

ITEM 622 - PORTABLE CONCRETE BARRIER, 32"

DURING EARTHWORK OPERATIONS THAT MAY AFFECT THE INTEGRITY OF THE SLOPE OR PAVEMENT AND DURING THE TIME REQUIRED TO REPLACE THE GUARDRAIL, THE CONTRACTOR SHALL USE PORTABLE CONCRETE BARRIER, 32" TO MOVE TRAFFIC OVER TO THE LEFT LANE.

A CONTINGENCY QUANTITY OF 1,700 LIN. FT. HAS BEEN INCLUDED IN THE EVENT THE CONCRETE BARRIER IS RELOCATED FROM THE LANE LINE TO THE RIGHT SHOULDER, THEREBY, OPENING TWO 12' LANES TO TRAFFIC. A MINIMUM 2' OFFSET BETWEEN THE BARRIER FACE AND THE TRAVELLED LANE MUST BE MAINTAINED.

THE FOLLOWING ESTIMATED QUANTITY IS CARRIED TO THE GENERAL SUMMARY TO BE USED AS OUTLINED ABOVE:

622 PORTABLE CONCRETE BARRIER, 32" 3,400 LIN. FT.

ITEM 626 - BARRIER REFLECTOR, TYPE B

THE FOLLOWING QUANTITY HAS BEEN CARRIED TO THE GENERAL SUMMARY TO DELINEATE THE PORTABLE CONCRETE BARRIER:

626 - BARRIER REFLECTOR, TYPE B 70 EACH

IV. MAINTENANCE OF TRAFFIC MATERIALS

A. SIGNS

SIGN DIMENSIONS AND SPECIFICATIONS, INCLUDING LETTER SIZES SHALL BE AS PROVIDED IN THE "MANUAL", OR IN DESIGN DRAWINGS PROVIDED BY THE DEPARTMENT OF TRANSPORTATION. THE SIGNS SHALL BE SUBJECT TO APPROVAL OF THE ENGINEER PRIOR TO THE START OF THE PROJECT.

B. SIGN SUPPORTS

SIGN SUPPORTS SHALL BE OF SUFFICIENT SIZE AND MASS AS TO FIRMLY SUPPORT THE SIGNS AT THE APPROPRIATE HEIGHT. SUPPORTS SHALL BE AS SHOWN ON THE STANDARD DRAWINGS.

C. FLASHING ARROWS

THE ELECTRICAL FLASHING ARROW SHALL BE OF TYPE A, AS SHOWN ON STANDARD DRAWING TC-35.10.

D. CONES

CONES SHALL BE LOCATED AS SHOWN IN THE "MANUAL" AND THE STANDARD DRAWINGS.

E. LIGHTING DEVICES

FLASHERS SHALL BE 12 VOLT BATTERY-OPERATED MODELS WITH 7 INCH DIAMETER YELLOW LENSES ILLUMINATED BY RAPID INTERMITTENT FLASHERS OF SHORT DURATION AND SHALL BE PLACED ON SIGNS USED FOR NIGHTTIME CLOSURES AS SHOWN IN THE STANDARD DRAWINGS.

V. PAYMENT

PAYMENT FOR PROVIDING, ERECTING, MAINTAINING AND REMOVING TEMPORARY MAINTENANCE OF TRAFFIC CONTROL DEVICES SHALL BE MADE UNDER THE LUMP SUM PRICE BID FOR ITEM 614 - MAINTAINING TRAFFIC.

PLOTTED BY: dstupkov
PLOTTED FROM: \\users\dstupkov\design\drainage\1\90-1786\plot.dgn 9/17/86/mt2.dgn
PLOT SUBMITTED: 08-JAN-1998 14:25

GENERAL NOTES

LAK-90-17.86