

QUANTITIES		FHWA REGION	STATE	PROJECT
CALCULATED	JcHc 5-88	5	OHIO	
CHECKED	JcDs 5-88			

19
38

LAKE COUNTY
LAK - 90 - 23.42 (L & R)

BARRIER REFLECTORS

STATIONING	SPACING	TYPE B RURAL		REMARKS
		W	Y	
<i>Item 614 Barrier Reflector, Type B</i>				
829+65.60 to 839+18.30	50' 9/c	20		Phase I, E.B.L.
829+62.53 to 839+08.00	50' 9/c		20	Phase I, W.B.L.
<i>Totals =</i>				
		40	40	On Temporary Concrete Barrier
<i>Item 802 Barrier Reflector, Type B</i>				
830+25 to 839+00	100' 9/c		10	Inside E.B.L.
830+25 to 839+00	100' 9/c	10		Outside E.B.L.
829+80 to 838+50	100' 9/c		10	Inside W.B.L.
829+80 to 838+50	100' 9/c	10		Outside W.B.L.
<i>Totals =</i>				
		20	20	On Bridge Safety Parapet

614 Barrier Reflectors

These reflectors and their mounting shall conform to Supplemental Specification 802 except that spacing shall be as shown in the subsummary table.