



GENERAL NOTES:

1. THE LOCATION OF THE TRANSITION TAPER AND THE ADVANCE WARNING SIGNS SHOULD BE ADJUSTED TO PROVIDE FOR ADEQUATE SIGHT DISTANCE FOR THE EXISTING VERTICAL AND HORIZONTAL ROADWAY ALIGNMENT.
2. THE SPACING BETWEEN PROPOSED SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND TO PROVIDE A MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS.
3. THE TAPER LENGTH (L), NUMBER (N), SPACING (S) OF DRUMS SHALL CONFORM TO TABLE I. DRUM SPACING (S) SHALL BE USED FOR THE PAVEMENT TAPER, THE BUFFER AREA AND FOR THE FIRST 1000 FEET OF THE WORK AREA AND AT OTHER HAZARDOUS LOCATIONS AS DIRECTED BY THE ENGINEER. THE MAXIMUM DRUM SPACING FOR THE BALANCE OF THE WORK AREA IS TO BE TWO TIMES THE SPACING (S) IN TABLE I. A MINIMUM OF 5 DRUMS SHALL BE USED IN THE SHOULDER TAPER AND THE DOWNSTREAM TAPER.
4. TYPE C STEADY BURNING WARNING LIGHTS SHALL BE ERECTED ON EACH DRUM FOR NIGHT CLOSURES.
5. CONES HAVING A MINIMUM HEIGHT OF 28 INCHES MAY BE SUBSTITUTED FOR DRUMS FOR DAYTIME LANE CLOSURES. PROVISIONS SHALL BE MADE TO SAFELY STABILIZE THE CONES TO PREVENT THEM FROM BLOWING OVER. IF THIS CANNOT BE ACHIEVED, DRUMS SHALL BE USED.

6. IF THE CONSTRUCTION OPERATION REQUIRES THE LANE CLOSURE FOR MORE THAN ONE DAY THEN THE EXISTING CONFLICTING PAVEMENT MARKINGS AND REFLECTORS FROM THE RAISED PAVEMENT MARKERS (RPM'S) SHALL BE REMOVED AND THE APPROPRIATE COLOR TEMPORARY EDGE LINES SHALL BE APPLIED ALONG THE TAPER. TEMPORARY EDGE LINES WHICH WOULD CONFLICT WITH FINAL TRAFFIC LANES SHALL BE REMOVABLE (947.03 TYPE-C) TAPE OR TEMPORARY RPM'S UNLESS THE AREA WILL BE RESURFACED IN THE NEXT WORK PHASE. AFTER COMPLETION OF THE WORK, TEMPORARY MARKINGS SHALL BE REMOVED IN ACCORDANCE WITH 621.34 AND THE ORIGINAL MARKINGS AND RAISED PAVEMENT MARKERS REFLECTORS SHALL BE RESTORED.
7. THE ADVISORY SPEED SIGN OW-143-24 SHALL BE USED WHEN SPECIFIED IN THE PLAN OR AS DIRECTED BY THE ENGINEER. THE ADVISORY SPEED SHALL BE AS SPECIFIED IN THE PLANS OR AS DIRECTED BY THE ENGINEER.
8. TYPE A FLASHING WARNING LIGHTS SHOWN ON THE "ROAD CONSTRUCTION AHEAD" AND "RIGHT LANE CLOSED AHEAD" SIGNS ARE REQUIRED WHENEVER A NIGHT LANE CLOSURE IS NECESSARY.
9. THE FLASHING ARROW PANEL SHALL MEET REQUIREMENTS OF STANDARD CONSTRUCTION DRAWING TC-35.10.

10. THE BARRIER TRUCK SHOWN AT THE BEGINNING OF THE WORK AREA SHALL BE IN PLACE AND UNOCCUPIED WHENEVER WORKERS ARE IN THE WORK AREA. THIS VEHICLE SHALL BE REMOVED FROM THE PAVEMENT WHENEVER WORKERS ARE NOT IN THE WORK AREA. OTHER PROTECTIVE DEVICES MAY BE USED IN LIEU OF THE BARRIER TRUCK SHOWN WHEN APPROVED BY THE ENGINEER. THE VEHICLE SHALL BE EQUIPPED WITH A 360 DEGREE ROTATING OR FLASHING AMBER BEACON CLEARLY VISIBLE A MINIMUM OF 1/4 MILE.
11. THE OC-8 SIGNS ARE ONLY REQUIRED FOR LANE CLOSURES OF MORE THAN ONE DAY AND MAY BE OMITTED IF THEY FALL WITHIN THE LIMITS OF A CONSTRUCTION PROJECT.

ALL MATERIAL AND EQUIPMENT SHALL BE REMOVED FROM WORK AREA WHEN NO WORK IS BEING DONE.

TABLE I

SPEED LIMIT MPH	MINIMUM TAPER (L) IN FEET	MINIMUM NUMBER (N) OF DRUMS	MAXIMUM SPACING (S) OF DRUMS
20-25	125	6	20
30-40	320	9	40
45-55	660	13	60

ALL WORK AND TRAFFIC CONTROL DEVICES SHALL BE IN ACCORDANCE WITH 614 AND OTHER APPLICABLE PORTIONS OF THE C & M SPECIFICATIONS AS WELL AS IN ACCORDANCE WITH PART 7 OF ODOT. PAYMENT FOR ALL LABOR, EQUIPMENT AND MATERIALS TO PROVIDE THIS METHOD OF TRAFFIC CONTROL SHALL BE INCIDENTAL TO THE LUMP SUM BID FOR 614 MAINTAINING TRAFFIC, UNLESS SEPARATELY ITEMIZED IN THE PLAN.

BUREAU OF DESIGN SERVICES DIVISION OF HIGHWAYS OHIO DEPARTMENT OF TRANSPORTATION		DATE
MAINTENANCE OF TRAFFIC CLOSING RIGHT LANE OF A MULTI-LANE UNDIVIDED HIGHWAY WITH DRUMS		10/10/88
STANDARD CONSTRUCTION DRAWING MT-95.31		
APPROVED: <i>[Signature]</i> ENGR. OF DESIGN SERVICES		