

RECORD OF SURVEYS,

Plat of *Survey*

No. *41*


Town *Willoughby* (*9*), Range *10*

Survey made *Oct 28-29-30-31* & *Nov 1-2-3* 1895, at the request of *County Commissioners*
For the purpose of locating the center of the Cleveland road from the County line to the west line of the Village of Willoughby

by *Frank M. Barber*

County Surveyor.

Viewers
Surveyors report to County Commissioners. **DESCRIPTION.**

To the Hon. Commissioners of Lake County Ohio Gentlemen—
Your Committee appointed by your honorable board met as directed, on Oct 28-1895- we took to our assistance *Mahlon Sweet & Warren Hoese* Chairman, and *Albert Woodard* marker. after taking an oath to faithfully & impartially perform the several duties assigned to us. we proceeded to locate & find the center of the Cleveland road (Euclid Avenue) beginning at the west line of Lake County where we found (3) three monuments one in the center of the road & one at proper distance on either side thence *N 49° 23' E 674* ft where we found an angle & placed two stone monuments one on each side .30 feet from center of the road thence *N 47° 15' E 815* ft where we found a monument in the center of road, we also placed side monuments 30 ft from center. thence *N. 47° 30' E 1379* ft we found an angle & placed side monuments 30 feet from center of the road. thence *N. 47° 40' E 1385* feet from the center of the road. thence *N 44° 18' E 2382* ft. where we found an angle-intersection of angle made & side monuments set. thence *N 44° 36' E 2789* ft we found a stone in center of road & placed monuments at proper distance each side. thence *N 46° 52' E 2230* ft reced monument by record found in Vol A-Page 345 & 346 & 347. (Road book) thence *N. 61° 04' E 3753* ft found stone set in side stones proper distance from center. thence *N 74° 05' E* we found gas pipe stake in center of road & at the intersection of Fowler road—thence *N 74° 04' E 1044* ft found gas pipe at angle & set side stones proper distance from center on each side of road. thence *N 52° 28' E 144* ft found gas pipe stake at angle & we set side stones at proper distance from center of road. thence *N 44° 58' E 1718* feet found stone in center of the road marked thus □. & on the west line of Willoughby Village & recorded in book B Page 61 - Side stones set at proper distance on either side of the Road. The stone monuments we set are (3) three feet in length and marked thus □  Note all angles plotted all of which we respectfully submit to your honorable board

E. M. Woodard
M. E. Sweet
W. L. Hoese

CALCULATIONS.

Sta.	Course.	Distance.	Latitude.		Departure.		Double Longitude.	Double Areas.		REMARKS.
			North.	South.	East.	West.		North.	South.	

I, *Frank M. Barber* County Surveyor of Lake County, Ohio, do hereby certify, that I have surveyed and subdivided Lot. No. in Tract No. Township of in accordance with the statutes of Ohio, and the laws of the United States. Surveyed pursuant to the application of *the County Commissioners* and *Oct 28, 29, 30, 31* & *Nov 1-2-3* A. D. 1895
Frank M. Barber County Surveyor.

Albert Woodard } *Flagmen.*
 } *Marker.*

M. E. Sweet
Warren Hoese } *Tapemen.*

LAKE COUNTY, OHIO.

