

REV STORM SEWER CONN

REV PER BUILDER

UPDATED OWNERS

DESCRIPTION

CL

CL


BY

5/21/14

2/14/14

1/6/14

NO. DATE



INLET PROTECTION IN SWALES.
DITCH LINES OR YARD INLETS
NOT TO SCALE

1, INLET PROTECTION SHALL BE CONSTRUCTED EITHER BEFORE UPSLOPE LAND DISTURBANCE BEGINS OR BEFORE THE INLET BECOMES FUNCTIONAL.

2. THE EARTH AROUND THE INLET SHALL BE EXCAVATED COMPLETELY TO A DEPTH AT LEAST 18 INCHES.

3. THE WOODEN FRAME SHALL BE CONSTRUCTED OF 2-INCH BY 4-INCH CONSTRUCTION GRADE LUMBER. THE 2-INCH BY 4-INCH, POSTS SHALL BE DRIVEN ONE (1) FT, INTO THE GROUND AT FOR CORNERS OF THE INLET AND THE TOP PORTION OF 2-INCH BY 4-INCH FRAME ASSEMBLED USING THE OVERLAP JOINT SHOWN. THE TOP OF THE FRAME SHALL B4E AT LEAST 6 INCHES BELOW ADJACENT ROADS IF PONDED WATER WILL POSE A SAFETY HAZARD TO TRAFFIC.

4. WIRE MESH SHALL BE OF SUFFICIENT STRENGTH TO SUPPORT FABRIC WITH WATER FULLY IMPOUNDED AGAINST IT. IT SHALL BE STRETCHED TIGHTLY AROUND THE FRAME AND FASTENED SECURELY TO THE FRAME.

5. GEOTEXTILE MATERIAL SHALL HAVE AN EQUIVALENT OPENING SIZE OF 20-40 SIEVE AND BE RESISTANT TO SUNLIGHT. IT SHALL BE STRETCHED FROM THE TOP OF THE FRAME TO 18 INCHES BELOW THE INTLET NOTCH ELEVATION. THE GEOTEXTILE SHALL OVERLAP ACROSS ONE SIDE OF THE INLET SO THE ENDS OF THE CLOTH ARE NOT FASTENED TO THE SAME POST.

6. BACKFILL SHALL OVERLAP ACROSS ONE SIDE OF THE INLET SO THE ENDS OF THE CLOTH ARE NOT FASTENED TO THE SAME POST.

6. BACKFILL SHALL BE PLACED AROUND THE INLET IN COMPACTED 6-INCH LAYERS UNTIL THE EARTH IS EVEN WITH NOTCH ELEVATION ON ENDS AND TOP ELEVATION ON SIDES.

7. A COMPACTED EARTH DIKE OF CHECK DAM SHALL BE CONSTRUCTED IN THE DITCH LINE SHALL BE AT LEAST 6-INCHES HIGHER THAN THE TOP OF THE FRAME.

STRAW BALES MAY BE USED IN CONJUNCTION WITH BUT NOT IN PLACE OF SILT FENCE INLET PROTECTION

1. SILT FENCE SHALL BE CONSTRUCTED BEFORE UPSLOPE LAND DISTURBANCE BEGINS.
2. ALL SILT FENCE SHALL BE PLACED AS CLOSE TO THE CONTOUR AS POSSIBLE SO THAT WATER WILL NOT CONCENTRATE AT LOW POINTS IN THE FENCE AND SO THAT SMALL SWALES OR DEPRESSIONS THAT MAY CARRY SMALL CONCENTRATED FLOWS TO THE SILT FENCE ARE DISSIPATED ALONG ITS LENGTH.
3. ENDS OF THE SILT FENCES SHALL BE BROUGHT UPSLOPE SLICHTLY SO THAT WATER PONDED BY THE SILT FENCE WILL BE PREVENTED FROM FLOWING AROUND THE ENDS.
4. SILT FENCE SHALL BE PLACED ON THE FLATTEST AREA AVAILABLE.
5. WHERE POSSIBLE, VEGETATION SHALL BE PRESERVED FOR 5 FEET (OR AS MUCH AS POSSIBLE) UPSLOPE FROM THE SILT FENCE. IF VEGETATION IS REMOVED, IT SHALL BE REESTABLISHED WITHIN 7 DAYS FROM THE INSTALLATION OF THE SILT FENCE.
6. THE HEIGHT OF THE SILT FENCE SHALL BE A MINIMUM OF 16 INCHES ABOUVE THE ORIGINAL GROUND SURFACE.

S. THE HEIGHT OF THE SILT FENCE SHALL BE A MINIMON OF TO TROICES DOES TO THE SILT FENCE SHALL BE PLACED IN AN EXCAVATED OR SLICED TRENCH CUT A MINIUM OF 8 INCHES DEEP, THE TRENCH SHALL BE MADE WITH A TRENCHER, CABLE LAYING MACHINE, SLICING MACHINE, OR OTHER SUITBALE DEVICE THAT WILL ENSURE AN ADQUIATELY UNIFORM TRENCH DEPTH.

8. THE SILT FENCE SHALL BE PLACED WITH THE STAKES ON THE DOWNSHOPE SIDE OF THE GEOTEXTILE. A MINIMUM OF 8 INCHES OF GEOTEXTILE MUST BE BELOW THE GROWND SURFACE. EXCESS MATERIAL SHALL LAY ON THE BOTTOM OF THE 6-INCH DEEP TRECH. THE TRENCH SHALL BE BACKFILLED AND COMPACTED ON BOTH SIDES OF THE FABRIC.

9. SEAMS BETWEEN SECTIONS OF SILT FENCE SHALL BE SPLICED TOGETHER ONLY AT A SUPPORT POST WITH A MINIMUM 6-INCH OVERLAP PRIOR TO DRIVING INTO THE GROWND.

10.MAINTENANCE-SILT FENCE SHALL ALLOW RUNGET TO PASS ONLY AS DIFFUSE FLOW THROUGH THE GETOTEXTILE. IF RUNGET OVERTOPS THE SILT FENCE, FLOWS UNDER THE FABRIC OR AROUND THE FENCE ENDS, OR IN ANY OTHER WAY ALLOWS A CONCENTRATED FLOW DISCHARGE, ONE OF THE FOLLOWING SHALL BE PERFORMED, AS APPROPRIATE: 1) THE LAYOUT OF THE SILT FENCE SHALL BE CHANGED, 2) ACCUMULATED SEDIMENT SHALL BE REMOVED, OR 3) OTHER PRACTICES SHALL BE INSTALLED.

SEDIMENT DEPOSITS SHALL BE ROUTINELY REMOVED WHEN THE DEPOSIT REACHES APPROXIMATELY ONE—HALF OF THE HEIGHT OF THE SILT FENCE.

SILT FENCES SHALL BE INSPECTED AFTER EACH RAINFALL AND AT LEAST DAILY DURING A PROLONGED RAINFALL. THE LOCATION OF EXISTING SILT FENCE SHALL BE REVIEWED DAILY TO ENSURE ITS PROPER LOCATION AND EFFECTIVENESS. IF DAMAGED, THE SILT FENCE SHALL BE REPAIRED IMMEDIATELY.

CRITERIA FOR SLT FENCE MATERIALS

1.FENCE POSTS—THE LENGTH SHALL BE A MINIMUM OF 32 INCHES. WOOD POSTS WILL BE 2-BY-2-IN.

TRENCH TO BE NOMINAL DIMENSIONED HARDWOOD OF SOUND QUALITY. THEY SHALL BE FREE OF KNOTS, SPLITS AND OTHER HARDWOOD OF SOUND QUALITY. THEY SHALL BE FREE OF KNOTS, SPLITS AND OTHER MAXIMUM SPACING BETWEEN POSTS SHALL BE OWNERFLED TO FEET. POSTS SHALL BE DRIVEN A MINIMUM 16 INCHES INTO THE GROUND, WHERE POSSIBLE. IF NOT POSSIBLE, THE POSTS SHALL BE ADEQUATELY SECURED TO PREVENT OVERTURNING OF THE FENCE DUE TO

FABRIC PROPERTIES		TEST METHOD
MINIMUM TENSILE STRENGTH	120 LBS. (535 N)	
MAXIMUM ELONGATIONAT 60 LBS.	50 X	
MINIMUM PUNCTURE STRENGTH	50 LBS. (220 N)	
MINIMUM TEAR STRENGTH	40 LBS. (180 N)	
		ASTM D 4751
MINIMUM PERMITTIVITY	1X10-2 SEC-1	
THE EVONOURE CORNECTE RETENTION	1 70 %	ASTM G 4355

TEMPORARY SEEDING

SEEDING DATES	SPECIES	Lb./1,000 S.F.	LB/PER ACRE
MARCH 1 - AUGUST 15	OATS TALL FESCUE ANNUAL RYEGRASS	3. 1 1	128 (4 BUSHEL) 40 40
	PERENNIAL RYEGRASS TALL FESCUE ANNUAL RYEGRASS	1 1	40 40 40
	ANNUAL RYEGRASS PERENNIAL RYEGRASS CREEPING RED FESCUE KENTUCKY BLUEGRASS	1.25 3.25 0.4 0.4	55 142 17 17
	OATS TALL FESCUE ANNUAL RYEGRASS	3 1	128 (3 BUSHEL) 40 40
AUGUST 16 - NOVEMBER	RYE TALL FESCUE ANNUAL RYEGRASS	1	112 (2 BUSHEL) 40 40
	WHEAT TALL FESCUE ANNUAL RYEGRASS	3 1 1	120 (2 BUSHEL) 40 40
	PERENNIAL RYEGRASS TALL FESCUE ANNUAL RYEGRASS	1	40 40 40
	ANNUAL RYEGRASS PERENNIAL RYEGRASS CREEPING RED FESCUE KENTUCKY BLUEGRASS	1,25 3,25 0,4 0,4	40 40 40
NOVEMBER 1 - FEB. 29	USE MULCH ONLY OR D	COLLEGE CCCOMO	And the second s

1. STRUCTURAL EROSION AND SEDIMENT CONTROL PRACTICES SUCH AS DIVERSIONS AND SEDIMENT TRAPS SHALL BE INSTALLED AND STABILIZED WITH TEMPORARY SEEDING PRIOR TO GRADING THE REST OF THE CONSTRUCTION SITE.

2. TEMPORARY SEED SHALL BE APPLIED BETWEEN CONSTRUCTION OPERATIONS ON SOIL THAT WILL NOT BE GRADED OR REWORKED FOR 21 DAYS OR GREATER. THESE IDLE AREAS SHALL BE SEEDED WITHIN 7 DAYS AFTER GRADING.

3. THE SEEDBED SHOULD BE PULVERIZED AND LOOSE TO ENSURE THE SUCCESS OF ESTABLISHING VEGETATION, TEMPORARY SEEDING SHOULD NOT BE POSTPONED IF IDEAL SEEDBED PREPARATION IS NOT POSSIBLE.

4. SOIL AMENDMENTS—TEMPORARY VEGETATION SEEDING RATES SHALL ESTABLISH ADEQUATE STANDS OF VEGETATION, WHICH MAY REQUIRE THE USE OF SOIL AMENDMENTS. BASE RATES FOR LINE AND FERTILIZER SHALL BE USED.

5. SEEDING METHOD—SEED SHALL BE APPLIED UNIFORMLY WITH A CYCLONE SPREADER, DRILL, CULTPACKER SEEDER, OR HYDROSEEDER. WHEN FEASIBLE, SEED THAT HAS BEEN BROADCAST SHALL BE COVERED BY RAKING OR DRAGGING AND THEN LIGHTLY TAMPED INTO PLACE USING A ROLLER OR CULTPACKER. IF HYDROSEEDING IS USED, THE SEED AND FERTILIZER WILL BE MIXED ON—SITE AND THE SEEDING SHALL BE DONE IMMEDIATELY AND WITHOUT INTERRUPTION.

MULCHING TEMPORARY SEEDING

WITHOUT INTERRUPTION.

MULCHING TEMPORARY SEEDING

1, APPLICATIONS OF TEMPORARY SEEDING SHALL INCLUDE MULCH, WHICH SHALL BE
APPLIED DURING OR IMMEDIATELY AFTER SEEDING, SEEDINGS MADE DURING OPTIMUM
SEEDING DATES ON FAVORABLE, AFTER SEEDING, SEEDINGS MADE DURING OPTIMUM
SEEDING DATES ON FAVORABLE AFTER SEEDING, SEEDINGS MADE DURING OPTIMUM
SEEDING DATES ON FAVORABLE AFTER SEEDING, SEEDINGS MADE DURING OPTIMUM
SEEDING DATES ON FAVORABLE TON.

2. MATERIALS:

-STRAW-IF STRAW IS USED, IT SHALL BE UNROTTED SMALL—GRAIN STRAW APPLIED AT A
RATE OF 2 TONS PER ACRE OR 90 LBS./1,000 SQ.FT. (2-3 BALES)

-HYDROSEEDERS-IF WOOD CELLULOSE FIBER IS USED, IT SHALL BE USED AT 2000

LBS./AC. OR 46 LB./1,000-SQ.FT.

-OTHER-OTHER ACCEPTABLE MULCHES INCLUDE MULCH MATTINGS APPLIED ACCORDING TO
MANUFACTURER'S RECOMMENDATIONS OR WOOD CHIPS APPLIED AT 6 TON./AC.

3. STAW MULCH SHALL BE ANCHORED IMMEDIATELY TO MINIMIZE LOSS BY WIND OR WATER.
ANCHORING METHODS:

-MECHANICAL—A DISK, CRIMPER, OR SIMILAR TYPE TOOL SHALL BE SET STRAIGHT TO
PUNCH OR ANCHOR THE MULCH MATERIAL INTO THE SOIL. STRAW MECHANICALLY
ANCHORED SHALL NOT BE FINELY CHOPPED BUT LEFT TO A LENGTH OF APPROXIMATELY 6
INCHES.

-MULCH NETTING—NETTING SHALL BE USED ACCORDING TO THE MANUFACTURERS
RECOMMENDATIONS. NETTING MAY BE USED ACCORDING TO THE MANUFACTURERS
RECOMMENDATIONS. NETTING MAY BE USED ACCORDING TO THE MANUFACTURERS
RECOMMENDATIONS. NETTING MAY BE NECESSARY TO HOLD MULCH IN PLACE IN AREAS OF
CONCENTRATED RUNOFF AND ON CRITICAL SLOPES.

-SYNTHETIC BINDERS—SYNTHETIC BINDERS SUCH AS ACRYLIC DLR (AGRI-TAC), DCA-70,
PETROSET, TERRA TRACK OR EQUIVALENT MAY BE USED AT RATES RECOMMENDED BY THE
MANUFACTURER.

-WOOD—CELLULOSE FIBER—WOOD—CELLULOSE FIBER BINDER SHALL BE MIXED WITH WATER AND
THE MIXTURE SHALL CONTAIN A MAXIMUM OF 50 LB./100 GAL.

Stormwater Management Plan Approved as shown and/or noted JAMES R. GILLS, P.E. County Drainage Engineer L.S. Date 5/22/14

5425 WARM VALLEY VII 440-6 SITUATED IN THE VILLAGE OF KIRTLAND HILLS, COUNTY OF LAKE, STATE OF OHIO

BEING PART OF LOTS 5 & 6, SHEHI TRACT

IN ORIGINAL MENTOR TOWNSHIP

RINER ROAD - SUITE 12 /IEW, OHIO 44125 602-9071 FAX 216-369-0259	HORIZ. SCALE: 1" = 30'	VERT. SCALE:
TECH	DRAWN BY: CL	DATE: 11/14/2013
	CHECKED BY: SRL	DRAWING NO.: 20132851
NGINEERING and SURVEYING Civil Engineering Land Surveying	JOB NO.: 20132851	SHEET: 1 OF 2