



I-15 GUARD RAIL

REF. NO.	STATIONS	SIDE	STANDARD
1-G	204+00 TO 206+95	L	296.0
2-G	204+00 TO 206+95	R	292.5
TOTALS			588.5

EXCAVATION	7,751 C.Y.
EMBANKMENT	8,332 C.Y.
EMB. @ 18%	9,832 C.Y.
SEED & PROTECT	33,717 SQ.Y.

EXCAVATION	3,980 C.Y.
EMBANKMENT	9,478 C.Y.
EMB. @ 18%	11,184 C.Y.
SEED & PROTECT	23,994 SQ.Y.

STORM SEWERS

REF. NO.	STATION	SIDE	CLASS		UNDERDRAIN	PAV'T.	MATERIAL	EACH		TOTAL
			I-4	I-5				CONC. REINF. EXCAV.	FOR STEEL STRUC.	
1-F	204+00	L	834	8	1					
2-F	204+00	L	1302	16	1					
3-F	204+00	R	1298	16	2					
4-F	204+00	R	874							
5-F	215+96	R	104							
TOTALS			4412	40	4					18012.8

6" UNDERDRAINS

REF. NO.	STATION	SIDE	I-4	I-5	I-5 EACH
1-F	204+00	L	834	8	1
2-F	204+00	L	1302	16	1
3-F	204+00	R	1298	16	2
4-F	204+00	R	874		
5-F	215+96	R	104		
TOTALS			4412	40	4

PLAN & PROFILE - LAKELAND FREEWAY - STA. 204+00 TO STA. 217+00