

# BRIDGE DATA

PART NUMBER :	①	②	③	④
BRIDGE NUMBER :	LAK-2-0055L	LAK-2-0055R	LAK-2-0180L	LAK-2-0180R
LOCATION :	LLOYD RD RAMP UNDER SR-2	LLOYD RD RAMP UNDER SR-2	E 305TH ST UNDER SR-2	E 305TH ST UNDER SR-2
MIN VERTICAL CLEARANCE	15.00'	14.83'	16.92'	15.00'
OVERALL LENGTH	170.00'	170.00'	158.00'	158.00'
NUMBER OF SPANS	3	3	3	3
LONGEST SPAN	70.00'	70.00'	73.00'	73.00'
GIRDER SIZE	36WF150 36WF182	36WF150 36WF182	36WF150 36WF230	36WF150 36WF230
ROADWAY WIDTH ON BRIDGE	64.0'	54.0'	52.8'	52.8'
NUMBER OF LANES UNDER BRIDGE	1NB, 1SB	1NB, 1SB	3NB, 2SB	2NB, 3SB
UTILITIES CARRIED BY STRUCTURE	NONE	NONE	NONE	NONE
NUMBER OF GIRDERS	9	9	7	7
% MISC. STEEL	21%	21%	23%	23%

**NOTE:** THE PERCENT MISCELLANEOUS STEEL FOR EACH BRIDGE REPRESENTS, APPROXIMATELY, THE PERCENTAGE OF THE TOTAL STEEL SURFACE AREA REQUIRED FOR MISCELLANEOUS STEEL (i.e. CROSSFRAMES, etc.)

PLOTTED BY: nma | jay  
 PLOTTED FROM: i:\buser\mml\lloyd.dgn  
 FILENAME: d:\20055\bestimate.dgn  
 PLOT SUBMITTED: 24-FEB-1999 14:29

	OHIO DEPARTMENT OF TRANSPORTATION DISTRICT 12 BRIDGE DEPT.
DATE 10-94	REVIEWED GWM
DRAWN MPC	REVISION STRUCTURE FILE NUMBER VARIOUS
DESIGNED MJM	CHECKED BCW
BRIDGE DATA	
LAK-2-00.55 & VAR.	
8 15	