



CURVE DATA
P.I. Sta. 546 + 44.64
 $\Delta = 39^{\circ}09'30''$ Rt.
 $D_c = 1^{\circ}30'00''$
 $R_c = 3819.71'$
 $L_c = 2410.55'$
 $T_c = 200.00'$
 $E_c = 1458.75'$
 $E_s = 234.91'$

Grate Elev. Std. # 4 C.B. Sta. 563 + 25 624.37
15" I-2 @ Std. # 4 C.B. Sta. 563 + 25 622.20
8" I-2 @ Std. # 4 C.B. Sta. 563 + 25 622.78
15" I-2 @ Outlet 622.06

MICROFILMED
JUL 1 1985

REF. NO.	STATION	SIDE	EXC FOR STRUCT. C.Y.	CLASS "A" STORM UNDER PAVT. SEC. M-6.8 (b) OR M-6.4 (c)	PIPE UNDER DRAINAGE		I-4	I-5	I-10	S-1	S-4	I-8
					6" SHALLOW	8" DEEP						
I-D	555+00	LT	1009	1009	10	10						
2-D	555+00	RT	1025	1025								
3-D	556+00		306	306								
4-D	559+89	LT	606	606								
5-D	559+89	RT	606	606								
6-D	563+25											

REF. NO.	STATION	SIDE	EXC FOR PAVT. C.Y.	CLASS "A" STORM UNDER PAVT. SEC. M-6.8 (b) OR M-6.4 (c)	SUBBASE		I-15
					15" SUBBASE	8" SUBBASE	
I-P	555+00	LT	401.47	401.47	401.47	401.47	
	557+96.44	LT	66.91	66.91	66.91	66.91	
	563+25	LT	312.5	312.5	312.5	312.5	
	563+25	RT	187.5	187.5	187.5	187.5	
	563+25	RT	25	25	25	25	
	TOTAL		3125	3125	3125	3125	

Excavation	2,035 C.Y.
Subbase	13,280 C.Y.
Pavement	15,936 C.Y.