



(D) DRAINAGE

REF. STATION NO.	CLASS "A" STORM SEWER UNDER PAVT. SEC. M-65(b) OR SEC. M-68(b)	8" OUTLET PIPE SEC. M-64(c)	6" PIPE UNDER DRAIN SHALLOW DEEP	6" TEE INCREASED OR	6"x8" TEE SEC. M-65(b)	STD. #4 CATCH BASIN	STD. #6 BASIN	L-10 SODDING	S-1 CONC. STRUCT. CL "C"	S-4 REINF. STEEL STRUCT.	E-2 EXC. FOR STRUCT.	E-3 CHANNEL FOR EXC.	S-24 REMOVAL OF EXIST. STRUCT. LUMP
FROM TO	L.F.	L.F.	SHALLOW DEEP	EACH	EACH	EACH	EACH	S.Y.	C.Y.	LBS.	C.Y.	C.Y.	Lump
1-D 595+00 597+60	LT.	10	288	1	1								
2-D 599+21 605+00	LT.	10	1006	1	1								
3-D 595+00 605+00	LT.	44	1022	2									
4-D 595+00 599+24	RT.		424										
5-D 595+00 599+24	RT.		302										
6-D 601+98 603+00	RT.							56	3.1	146	6		
7-D 595+00		98						54					
8-D 602+00		60											
9-D 595+00 599+23.72	RT.												
10-D 603+00 604+00	LT.												9811

(P) PAVEMENT

REF. STATION NO.	FROM TO	10" REINF. PORT. CEM. CONC. PAVT. S.Y.	I-22 SUB-BASE C.Y.	E-1 COMPACT. SUB-GRADE S.Y.
1-P 595+00 597+89.75	LT.	346.35	57.72	346.35
2-P 595+00 599+23.72	RT.	241.63	40.27	241.63

Excavation	13,211 C.Y.
Embankment	13,632 C.Y.
Embankment - 20'	16,358 C.Y.