

**LEGEND**

\* - (PARAPET) @ 12" C/C

**NOTES**

1. MINIMUM BAR LAPS:  
#4 BARS = 23" #5 BARS = 29" #6 BARS = 52" #8 BARS = 87"
2. FOR BEAM DETAILS AND NOTES SEE SHEET 21/44 .
3. TRANSVERSE CONSTRUCTION JOINTS SHALL NOT BE PERMITTED IN THE DECK SLAB.
4. FOR TRANSVERSE SECTION INCLUDING LONGITUDINAL BAR SPACING AND SCREED ELEVATION TABLE AND ADDITIONAL NOTES SEE SHEET 30/44 AND 33/44 .
5. FOR ADDITIONAL LIGHT POLE PILASTER NOTES AND DETAILS SEE ODOT STANDARD DRAWING HL-20-14.
6. FOR LIGHTING PLANS SEE SHEETS 1240 AND 1241 OF 1679 .
7. FOR INSIDE PARAPET PANEL DETAILS SEE SHEET 31/44 .
8. FOR CONTROL JOINTS FOR CONCRETE PARAPETS, SEE STANDARD DRAWING SBR-1-99.
9. PARAPET REINFORCING SHALL BE SPACED TO AVOID CONTROL JOINTS.



DESIGN AGENCY  
ARCADIS U.S., INC.  
100 Superior Avenue, Suite 1250 Cleveland, Ohio 44114  
Tel: 216-781-6177 Fax: 216-781-6245 www.arcadis-us.com

REVIEWED  
RBB  
DATE  
5/07

DRAWN  
MPB  
DESIGNED  
SKS  
CHECKED  
CMD

SLAB PLAN (RIGHT STRUCTURE)  
BRIDGE NO. LAK-2-0363 L&R  
STATE ROUTE 2 OVER EAST 361 ST STREET

LAK-2-3.32  
PID 13486

32 / 44

1303  
1679

