



PROP. 450 mm PULLBOX, PB7
STA 1+668.3, 7.6 m R

PROP. 51 mm CONDUIT RISER
FOR LOOP LEAD-IN
STA 1+671.2, 7.9 m R

PROP. SIGNAL SUPPORT, P1,
TYPE TC-81.20, DES. 4, 8.8 m ARM WITH
PEDESTRIAN SIGNAL & PUSHBUTTON
STA 1+623.2, 9.5 m R

PROP. 450 mm PULLBOX, PB1
STA 1+620.2, 13.0 m R

PROP. 300mm x 600mm PULLBOX, PB2
STA 1+607.5, 10.1 m R

PROP. CONTROLLER, WITH
FOUNDATION AND WORK PAD
STA 1+605.7, 15.3 m R

PROP. SIGNAL SUPPORT, P2,
TYPE TC-81.20, DES. 4, 10.4 m ARM WITH
PEDESTRIAN SIGNALS & PUSHBUTTONS
STA 1+605.3, 7.9 m R

PROP. 51 mm CONDUIT
RISER FOR POWER
STA 1+022.8, 6.4 m R

PROP. 51 mm CONDUIT RISER
FOR INTERCONNECT
STA 1+604.2, 7.9 m R

REMOVE EX. POLE MOUNTED CONTROLLER
STA 1+604.2, 7.8 m R

PROP. 51 mm CONDUIT RISER
FOR LOOP LEAD-IN
STA 1+572.6, 7.6 m R

PROP. 450 mm PULLBOX, PB6
STA 1+570.5, 7.0 m R

PROP. 51 mm CONDUIT RISER
FOR INTERCONNECT
STA 1+668.4

PROP. 2.4 m PEDESTAL, P4,
PEDESTRIAN SIGNALS & PUSHBUTTONS
STA 1+651.4, 9.2 m L

PROP. 450 mm PULLBOX, PB5
STA 1+648.2, 10.5 m L

PROP. SIGNAL SUPPORT, P3,
TYPE TC-81.20, DES. 2, 8.4 m ARM WITH
PEDESTRIAN SIGNALS & PUSHBUTTONS
STA 1+616.9, 9.5 m L

PROP. 450 mm PULLBOX, PB4
STA 1+620.2, 11.7 m L

PROP. 450 mm PULLBOX, PB3
STA 1+555.7, 7.9 m L

ALL HEADS ARE 300mm POLYCARBONATE