



PAVEMENT MARKING LEGEND

- (A) LANE LINE
- (B) CENTER LINE, SINGLE BROKEN
- (C) CHANNELIZING LINE
- (D) DOTTED LINE (White or Yellow)
- (E) CENTER LINE, DOUBLE SOLID
- (F) STOP LINES
- (G) CROSSWALK LINES
- (H) CENTERLINE, DOUBLE BROKEN, 1 SOLID
- (I) TRANSVERSE LINES
- (J) LANE ARROW
- (K) WORD "ONLY" ON PAVEMENT, 72"
- (L) SCHOOL SYMBOL MARKING, 72"
- (M) ISLAND MARKING, YELLOW
- (N) PARKING STALL MARKING
- (P) YELLOW EDGE LINE

LOOP	SIZE	Number of Turns	MODE	DELAY (SEC)	PHASE	Detector Unit
L 1	8' x 30'	2	PRESENCE	3	2	1
L 2	6' x 6'	3	PULSE		1	2
L 3	6' x 6'	3	PULSE		1	3
L 4	6' x 30'	2	PRESENCE		2	4
L 5	6' x 6'	3	PULSE		1	5
L 6	6' x 6'	3	PULSE		1	6

DETECTOR CHART

THE UNDERGROUND UTILITIES ARE SHOWN ACCORDING TO INFORMATION FURNISHED BY THE UTILITIES CONCERNED AND THE STATE DOES NOT GUARANTEE THE ACCURACY THEREOF.

TRAFF-PRO CONSULTANTS INC.
WILLOUGHBY, OHIO

STATE OF OHIO
DEPARTMENT OF TRANSPORTATION
U.S. 20 &
HOLLYCROFT LN. /
GARFIELD RD.

DESIGNED	DRAWN	TRACED	CHECKED	REVIEW DATE	REVISED

SIGNAL TIMING CHART

FUNCTION	Ø1	Ø2
MINIMUM GREEN	18	10
PED WALK	7	7
PED CLEARANCE	12	12
GREEN EXTENSION	4.0	3.0
MAXIMUM GREEN		3.0
YELLOW CLEARANCE	4.0	3.0
ALL RED CLEARANCE	1.0	1.5
RECALL	ON	OFF

SIGNAL DISPLAY CHART

SIGNAL HEAD	Ø1			Ø2			FLASH
	R	W	CLEAR	R	W	CLEAR	
A, B	R	R	R	G	G	Y	R
C, D	R	R	R	G	G	Y	R
E, F	G	G	Y	R	R	R	Y
G, H	G	G	Y	R	R	R	Y
R, S	DW	DW	DW	W	FDW	DW	DARK
T, U	DW	DW	DW	W	FDW	DW	DARK
V, W	W	FDW	DW	DW	DW	DW	DARK
X, Y	W	FDW	DW	DW	DW	DW	DARK

ALL 12" SIGNAL HEADS

TYPE D 2
DON'T WALK WALK