



- NOTE:**
1. ALL DIMENSIONS ARE GIVEN IN MILLIMETERS AND ALL ELEVATIONS ARE GIVEN IN METERS, UNLESS OTHERWISE INDICATED.
 2. FOR SECTIONS A-A, B-B AND D-D, SEE SHEET 7712.
 3. FOR DETAIL A, SEE SHEET 7712.
 4. REINFORCING STEEL IN THE VICINITY OF THE BRIDGE SEAT SHALL BE ACCURATELY PLACED TO AVOID INTERFERENCE WITH THE DRILLING OF BEARING ANCHOR HOLES OR THE PRE-SETTING OF BEARING ANCHORS.
 5. 600 mm POROUS BACKFILL SHALL EXTEND UP TO THE BOTTOM OF THE APPROACH SLAB OR TO 300 mm BELOW THE CONCRETE WALK.
 6. ABUTMENT CONCRETE ABOVE THE BRIDGE SEAT CONSTRUCTION JOINT SHALL NOT BE PLACED UNTIL THE PRESTRESSED CONCRETE BOX BEAM BEEN ERECTED.

- LEGEND:**
- | | |
|--------|----------------------|
| TYP. | TYPICAL |
| EXIST. | EXISTING |
| EL. | ELEVATION |
| C.J. | CONSTRUCTION JOINT |
| E.F. | EACH FACE |
| M.C. | MECHANICAL CONNECTOR |